

KOHLER® Roughing-In

K-1224-G, K-1224-GLF, K-1224-GRF MARIPOSA® 5.5' BUBBLEMASSAGE™ BATH

Product Information

Applicable products:	
Bubblemassage bath – drop-in	K-1224-G
Bubblemassage bath – 3-side integral flange, left drain	K-1224-GLF
Bubblemassage bath – 3-side integral flange, right drain	K-1224-GRF

Fixture*:	
Bathing well:	
Basin area, bottom	48" (1219 mm) x 24" (610 mm)
Basin area, top	59" (1499 mm) x 30" (762 mm)
Weight	100 lbs (45.4 kg)
To overflow:	
Water depth	14" (356 mm)
Capacity	67 gal (253.6 L)
* Approximate measurements for comparison only.	

Drop-in cut-out	64" (1626 mm) x 34" (864 mm)
-----------------	------------------------------

Blower motor:	Heater	V	Hz	A
	300 W	120	60	5

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI):	
Blower motor:	120 V, 15 A, 60 Hz
Blower motor is supplied with a 24" (610 mm) grounding-type plug-in cord.	

Installation Notes

Install this product according to the installation guide.

NOTICE: If the blower motor and check valve are relocated, two access panels are required. Locate one access panel at the blower motor/control location and the other at the control box. Locate the blower motor and check valve together.

Floor support under the bath must provide for a minimum of 86 lbs/square foot (418 kg/square meter) loading.

If used, the optional apron must be installed before the finished floor and wall materials are installed.

If installing a rim-mount faucet, make sure there is no interference with drain overflow and circulating system before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

Fixture conforms to tolerances in CSA B45.5/IAPMO Z124. All dimensions are nominal.

