

Lighting Your Life Since 1970

Product Specifications - 5849MROI			
Job Name:	Job Type:		
Quantity:	Comments		



5849MROI

Essentials 2-Light Flush Mount

N/A

N/A

N/A N/A N/A

Finish	Glass/Shade	Product Category
Oil Rubbed Bronze	Marble	Flush Mount

Measurements

Lamping	
Number of Bulbs	2
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	120
Rated Life	±2,500 Hours
Rated Lumens	±1,344
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A

Beam Spread

Dimmable

Photo Cell Included

Ballast/Driver/Transformer

CRI

2	Width
ndescent	Height
MB	Length
60	Extension
120	Back Plate Width
00 Hours	Back Plate Height
±1,344	HCO
±2,700 K	Min Overall Height
Included	Max Overall Height
N/A	Hanging Weight
N/A	Height Adjustable
N/A	Slope
N/A	Chain Length
No	Wire Length
Standard	Canopy Width
	Canopy Height
	Canopy Length

	Shipping	
11.50"	Carton Weight	2.20 lbs
6.00"	Carton Width	12'
N/A	Carton Height	6'
N/A	Carton Length	12'
N/A	Carton Cubic Feet	0.46
N/A	Master Pack	1
N/A	Master Pack Weight	N/A
N/A	Master Pack Width	N/A
N/A	Master Pack Height	N/A
2.20 lbs	Master Pack Length	N/A
N/A	Master Cubic Feet	N/A
N/A	UPS Shippable	Yes

Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209584907	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Iron		

Maxim Lighting International and all designs, logos and images © 2014 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.