

Lighting Your Life Since 1970

	Product Specifications - 13561CFAF					
I	Job Name:	Job Type:				
l						
ſ	Quantity:	Comments				
l						

4.6 lbs 17" 10" 18" 1.73 1

> N/A N/A N/A N/A Yes



13561CFAF Augusta 2-Light Flush Mount

Lamping	Measurements	Shipping
Finish Auburn Florentine	Glass/Shade Cafe	Product Category Flush Mount

Lamping		Measurements		Shipping
Number of Bulbs	2	Width	15.0"	Carton Weight
Light Type	Incandescent	Height	6.5"	Carton Width
Bulb Type	MB	Length	N/A	Carton Height
Max Bulb Wattage	75	Extension	N/A	Carton Length
Max Fixture Wattage	150	Back Plate Width	N/A	Carton Cubic Feet
Rated Life	±2,500 Hours	Back Plate Height	N/A	Master Pack
Rated Lumens	±1,600	HCO	N/A	Master Pack Weight
Color Temp	±2,700 K	Min Overall Height	N/A	Master Pack Width
Bulb(s)	Not Included	Max Overall Height	N/A	Master Pack Height
Light Up/Down	N/A	Hanging Weight	4.6 lbs	Master Pack Length
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet
CRI	N/A	Slope	N/A	UPS Shippable
Photo Cell Included	N/A	Chain Length	N/A	
Ballast/Driver/Transformer	No	Wire Length	N/A	
Dimmable	Standard	Canopy Width	N/A	
		Canopy Height	N/A	
		Canopy Length	N/A	

Certification		Other		Equivalents	
UL Standard	Dry	UPC Code	783209054042	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Steel		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.