

Lighting Your Life Since 1970

Product Specifications - 90328CLPB		
Job Name:	Job Type:	
Quantity:	Comments	



90328CLPB

Bound Glass 6-Light Chandelier

Finish Polished Brass

Lamping

Number of Bulbs	5+1
Light Type	Incandescent
Bulb Type	CA+MB R20
Max Bulb Wattage	40+50
Max Fixture Wattage	250
Rated Life	±1,500 Hours
Rated Lumens	±2,295
Color Temp	±2,500 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Glass/Shad	ϵ
Clear	

Measurements

Canopy Length

Wed3di ellielli3	
Width	17.5"
Height	16.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	9.9 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	36"
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A

Product Category

Single-Tier Chandelier

Shipping	
Carton Weight	9.9 lbs
Carton Width	19'
Carton Height	16"
Carton Length	20"
Carton Cubic Feet	3.42
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Certification		Other	
Safety Rating	Dry	UPC Code	783209000414
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Copper
		0.0040.14 . 1.14.	(; A D; (D

Equivalents

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.