

# INSTALLATION INSTRUCTION FOR 6361

## For Wall Mount Light Fixtures

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .  
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.**

READ AND SAVE THESE INSTRUCTIONS

### PREPARATION

1. Shut off the power at the fuse box or circuit breaker box. If necessary, remove the old fixture and all the mounting hardware from wall junction box.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.

### MOUNTING THE FIXTURE (FIG.1)

3. Secure circular strap (A) to outlet box (not provided) with outlet box screws (B) through slotted holes in circular strap.

### CONNECTING THE WIRES (Fig. 2)

4. Connect the fixture wires to the junction box wires as shown in Fig. 2. Make sure all wire connectors are secure and do not easily pull off with a slight tug. If there is no green ground wire from the junction box, connect the fixture ground wire to the circular strap or the crossbar with the green screw provided.
5. Tuck these wire connections neatly into the wall junction box.
6. Raise the face plate (C) to circular strap (A), and then secure face plate (C) with screws (D) using wrench (E).

### COMPLETING THE INSTALLATION

7. Install the proper light bulbs for your fixture.  
**(DO NOT EXCEED THE MAXIMUM WATTAGE RATING!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**
8. Place the outer glass (G) over the socket (F), and secure in place with retaining ring on the inner shade (H). Before inner shade (H) is tightened fully, adjust outer glass (G) until both appear parallel. Tighten inner shade (H) until snug.

Return the power to the junction box and test the fixture. Your installation is now complete.

