



Job Name:

Job Type:

Comments:

Quantity:

Product Number: 11128

Dimensions:



Diameter: 5 5/8"

Switch Type: N/A

Length: 13 1/2"

Mounting Proc.: Other

Width: 8 7/8"

Height: 7 5/8"

Bulbs:

- 1 - Medium Par30S 75w max 120v - Not included
- 1 - Medium Par30L 75w max 120v - Not included
- 1 - Medium Par30S 50w max 120v - Not included
- 1 - Medium BR-30 65w max 120v - Not included
- 1 - Medium Par30S 75w max 120v - Not included
- 1 - Medium Par30S 75w max 120v - Not included
- 1 - Medium Par30L 35w max 120v - Not included
- 1 - Medium Par30L 35w max 120v - Not included
- 1 - Medium Par30L 35w max 120v - Not included
- 1 - Medium Par30L 35w max 120v - Not included
- 1 - Medium Par30L 75w max 120v - Not included
- 1 - Medium Par30S 50w max 120v - Not included
- 1 - Medium Par30L 75w max 120v - Not included
- 1 - Medium Par30S 50w max 120v - Not included
- 1 - Medium BR-30 65w max 120v - Not included

Material List:

- 1 Housing - Steel/Aluminum - Raw Steel

Safety Listing:

- cUL Listed for Damp Locations / IC
- UL Listed for Damp Locations / IC

Instruction Sheets

11128 - IC Airtight 5" Housing

New Construction IC Airtight Housing

Trims: 11132AT, 11136AT, 11137AT, 11120AT, 11154AT, 11135AT, 11134AT, 11155AT, 11139AT, 11151AT, 11140AT

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.

Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.

Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.

Joist Tab: Tab to locate on bottom of joist.

Notch for T-Bar Ceilings: No clips required. Secure bar hanger to T-Bars with wires or screws.

Sealed Trim: One piece sealed trims. No light leaks.

Snap-In Socket: Snap in socket locates lamp in optimum position.

Quick Hit: Integral captive nails included and positioned for fast, easy installation.

Bar Hanger Locking Screw: Tighten screw to lock bar hangers in place.

Hinged Door: The hinged junction box door allows full access for wiring while remaining attached to the recess housing.

Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in, 4 out #12 wire, saves installation time.

UPC #: 785652111099

Product Type: Recessed
Light

Features:

Title 24

Trim



11120AT-15

5" Open Trim

White Steel Trim
 Maximum Wattage:
 75w Par30S



11132AT-14

5" Multiplier Trim

White Trim / Baffle Aluminum
 Baffle
 White Aluminum Trim
 Maximum Wattage:
 75w Par30L
 50w Par30S
 65w BR-30



11132AT-172

5" Multiplier Trim

Antique Bronze - White
 Aluminum Baffle
 White Aluminum Trim
 Maximum Wattage:
 75w Par30L
 50w Par30S
 65w BR-30



11132AT-22

5" Multiplier Trim

Polished Aluminum Aluminum
 Baffle
 White Aluminum Trim
 Maximum Wattage:
 75w Par30L
 50w Par30S
 65w BR-30



11132AT-71

5" Multiplier Trim

Antique Bronze Aluminum
 Baffle
 Antique Bronze Aluminum
 Trim
 Maximum Wattage:
 75w Par30L
 50w Par30S
 65w BR-30



11132AT-849

5" Multiplier Trim

Satin Nickel Aluminum Baffle
 Satin Nickel Aluminum Trim
 Maximum Wattage:
 75w Par30L
 50w Par30S
 65w BR-30



11132AT-861

5" Multiplier Trim

Satin Nickel - White Aluminum
 Baffle
 White Aluminum Trim
 Maximum Wattage:
 75w Par30L
 50w Par30S
 65w BR-30



11134AT-15

5" Shower Trim

Clear Glass Diffuser
 White Aluminum Reflector
 White Aluminum Trim
 Maximum Wattage:
 35w Par30L
 Suitable For Shower Light



11135AT-15

5" Shower Trim

Smooth White Glass Diffuser
 White Aluminum Reflector
 White Aluminum Trim
 Maximum Wattage:
 35w Par30L
 Suitable For Shower Light



11136AT-15

5" Eyeball Trim

White
 White Steel Trim
 Maximum Wattage:
 75w Par30S



11137AT-15

5" Regressed Eyeball Trim

White Steel Trim
 Maximum Wattage:
 75w Par30S



11139AT-15

5" Wall Wash Trim

White Steel Housing
 White Steel Trim
 Maximum Wattage:
 35w Par30L



11151AT-14

5" Baffle Trim

White Trim / Baffle Aluminum
 Baffle
 White Trim / Baffle Aluminum
 Trim
 Maximum Wattage:



11151AT-15

5" Baffle Trim

Black Aluminum Baffle
 White Aluminum Trim
 Maximum Wattage:
 75w Par30L
 50w Par30S



11154AT-14

5" Open Shower Trim

White Trim / Baffle Aluminum
 Baffle
 White Aluminum Trim
 Maximum Wattage:
 75w Par30L



11155AT-15

5" Shower Trim

Clear Glass Glass
 White Aluminum Reflector
 White Aluminum Trim
 Maximum Wattage:
 35w Par30L

| | | | |
|-------------------------|-------------------------|---|---------------------------|
| 50w Par30S 65w BR-30 | 50w Par30S 65w BR-30 | 50w Par30S Suitable For Shower Light | Suitable For Shower Light |
|-------------------------|-------------------------|---|---------------------------|

| Shipping Information | | | | | | | | | |
|----------------------|----------|----------------|--------|-------|--------|--------|--------|----------|--------|
| Package Type | Quantity | UPC | Length | Width | Height | Cube | Weight | UPS Ship | Label |
| Individual | 1 | 785652111099 | 14 | 11 | 7.5 | 0.668 | 2.2 | Yes | C IP-3 |
| Master Pack | 6 | 10785652111096 | 22.25 | 18.75 | 8.5 | 2.052 | 15.6 | Yes | A M-1 |
| NJ Pallet | 192 | | 48 | 40 | 73 | 81.111 | 499.2 | No | |
| NV Pallet | 192 | | 48 | 40 | 73 | 81.111 | 499.2 | No | |