



Job Name:

Job Type:

Comments:

Quantity:

Product Number: 1177LE

Dimensions:



Diameter: 6 1/4"
Length: 13 1/2"
Width: 12 5/16"
Height: 7 7/8"

Switch Type: N/A

Mounting Proc.: Other

Bulbs:

1 - G24q-1 4 - Pin 13w max 120v - Not included
1 - G24q-1 4 - Pin 13w max 120v - Not included
1 - G24q-1 4 - Pin 13w max 120v - Not included
1 - G24q-1 4 - Pin 13w max 120v - Not included
1 - G24q-1 4 - Pin 13w max 120v - Not included
1 - G24q-1 4 - Pin 13w max 120v - Not included
1 - G24q-1 4 - Pin 13w max 120v - Not included

Material List:

1 Housing - Steel/Aluminum -

Safety Listing:

UL Listed for Damp Locations / IC
cUL Listed for Damp Locations / IC

Instruction Sheets

English (HC-932)

1177LE - Fluorescent IC Airtight Housing

New construction fluorescent recessed lighting. UL listed for damp location with one class P HPF Electronic ballast. Bar hanger adjustable to 24 inches.

IC Airtight Fluorescent New Construction Recessed Housing.

Electronic Ballast; (Ref. Dim. 1128); uses trims 1157AT-14, 1157AT-15, 1160AT-14, 1160AT-22, 11061AT-172, 11061AT-861, 11063AT-15, 1135AT-15, 1133AT-15, and 1155AT-15.

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

Adjustable Socket Plate: Adjustable socket assembly provides flexibility in lamping options and precise lamp placement with various trims.

Housing Adjustment: Housing adjusts vertically for various ceiling thicknesses.

Bar Hanger: Break-away bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.

Quick Hit: Integral captive nails included and positioned for fast, easy installation.

Bar Hanger Locking Screw: Tighten screw to lock bar hangers in place.

Trouble-Free Ballast: Provided with integral ballast offering years of trouble-free operation.

Junction Box with Integral Romex Connector: Junction box with integral romex connector, quick-push and lock connector and through circuit wiring with 4 in, 4 out #12 wire, saves installation time.

Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.

UPC #: 785652011771

Product Type: Recessed
Light

Features:

Energy Star Compliant

Fluorescent

Title 24

Trim



11061AT-172
6" Deep Cone Multiplier T
 Antique Bronze - White Aluminum
 Baffle
 White Aluminum Trim
 Maximum Wattage:
 13w 4 - Pin



11061AT-861
6" Deep Cone Multiplier T
 Satin Nickel - White Aluminum
 Baffle
 White Aluminum Trim
 Maximum Wattage:
 13w 4 - Pin



11063AT-15
6" Wall Wash Trim
 White Steel Housing
 White Steel Trim
 Maximum Wattage:
 13w 4 - Pin



1133AT-15
Recessed Trim
 White Glass Diffuser
 White Plastic Trim
 Maximum Wattage:
 13w 4 - Pin
 Suitable For Shower
 Light



1135AT-15
6" Flat Glass Trim
 Smooth White Glass Diffuser
 White Steel Trim
 Maximum Wattage:
 13w 4 - Pin



1155AT-15
White Recessed Trim
 Clear Glass Glass
 White Aluminum Trim
 Maximum Wattage:
 13w 4 - Pin
 Suitable For Shower Light



1157AT-14
White Recessed Trim
 White Trim / Baffle Aluminum
 Baffle
 White Trim / Baffle Aluminum
 Trim
 Maximum Wattage:
 13w 4 - Pin



1157AT-15
**6" Deep Cone Baffle
 Trim**
 Black Aluminum Baffle
 White Aluminum Trim
 Maximum Wattage:
 13w 4 - Pin



1160AT-14
White Recessed Trim
 White Trim / Baffle Aluminum
 Reflector
 White Trim / Baffle Aluminum
 Trim
 Maximum Wattage:
 13w 4 - Pin



1160AT-22
6" Deep Cone Multiplier T
 Polished Aluminum Aluminum
 Reflector
 White Aluminum Trim
 Maximum Wattage:
 13w 4 - Pin

Replacement Bulb Data:

Product #		Type	Base	Watts	Watts Consumed	Volts	Hours	Lumens	Temp (°K)	CRI
97047		Quad 4-Pin	GX24q-1/GX24q-3	13	13	120v	10000	860	2700	
97047		Quad 4-Pin	GX24q-1/GX24q-3	13	13	120v	10000	860	2700	
97047		Quad 4-Pin	GX24q-1/GX24q-3	13	13	120v	10000	860	2700	
97047		Quad 4-Pin	GX24q-1/GX24q-3	13	13	120v	10000	860	2700	
97047		Quad 4-Pin	GX24q-1/GX24q-3	13	13	120v	10000	860	2700	
97047		Quad 4-Pin	GX24q-1/GX24q-3	13	13	120v	10000	860	2700	
97047		Quad 4-Pin	GX24q-1/GX24q-3	13	13	120v	10000	860	2700	

Shipping Information									
Package Type	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship	Label
Individual	1	785652011771	15.5	9	8	0.646	3.75	Yes	19 E-6 IP
Master Pack	6	10785652011778	26	18.5	9	2.505	25.2	Yes	17 E-2 M
NJ Pallet	144		48	40	72	80	604.8	No	
NV Pallet	144		48	40	72	80	604.8	No	