



Slimline[®] Bedpan Washer Regal[®] Model BPW-9000 Hydraulic BPW-9000 and BPW-9000-1.6 Models Flushometer

Description

Slimline® Bedpan Washer Regal® Water Closet Hydraulic Flushometer for floor mounted or wall hung top spud bowls.

Flush Cycle

Regal[®] Model BPW-9000 Water Saver (3.5 gpf/13.2 Lpf)

Regal[®] Model BPW-9000-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

Specifications

- Quiet, Exposed, Diaphragm Type, Chrome Plated Hydraulic Actuated Closet Flushometer with the following features:
- Stop Seat and Vacuum Breaker to be molded from PERMEX[™] rubber compound for Chloramine resistance
- ADA Compliant Non-Hold-Open feature type Actuator (specify Actuator) type listed below)
- 1" I.P.S. Screwdriver Bak-Chek™ Angle Stop
- Vandal Resistant Stop Cap
- Adjustable Tailpiece
- . Spud Coupling and Flange for 11/2" Top Spud
- Vacuum Breaker Flush Connection
- ٠ Low Consumption flush accuracy controlled by Para-Flo[™] Inside Parts Kit Bedpan Washer Diverter Assembly with the following features:
- Solid One-piece Body Construction
- Solid Brass Spray Arm
- Counter Balanced Pivot Assembly Diverter Valve Wall Support

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.6, and Military Specification V-29193.

- Actuator Types: (please check one)
 - FW Standard Fixture Wall Actuator (HY-33-A)

MP	Metal Partition Actuator (HY-49-A)

- SW Side Wall Mounted Actuator (HY-72-A)
- MBFW Metal Button Fixture Wall Actuator (HY-100-A)

See Hydraulic Flushometer Section of the Sloan catalog for additional information on Hydraulic Valves and Actuators.

Variations

F

- Bio-Gard[™] Spray Arm BG
- 🗌 ҮВ Sweat Solder Adapter
- 🗌 YI Two Wall Bumpers (for open front seat without cover)

REGAL XL

Flushometer includes Vandal Resistant Stop Cap with Set Screw, and Sweat Solder Adapter with Cover Tube and Cast Set Screw Wall Flange. See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.



This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.





SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL 60131 PHONE: 1-800-982-5839 • FAX: 1-800-447-8329 • http://www.sloanvalve.com