

SHC 4 Mini-tank Electric Water Heaters

- 6-year warranty on tank
- Glass-lined tank
- Wall mounted
- T & P valve included
- Plugs into standard 110-Volt outlet



ISO 9001

STIEBEL ELTRON

Simply the Best

800-582-8423

E-mail: info@stiebel-eltron-usa.com www.stiebel-eltron-usa.com

SHC 4 Mini-tank



Stiebel Eltron is a world leader in the development of advanced water heating technology. We have pursued engineering excellence and high quality over a period of several decades.

Commercial • Industrial • Institutional

- Office Buildings
- Stores
- Malls
- Warehouses
- Restaurants
 - Gas Stations
- Schools
- Hotels/Motels
- Commercial
- **Condominiums**
- Manufacturing **Facilities**

Residential

- Bathroom Sinks
- Kitchen Sinks
- Laundry Areas
- Cabins/Cottages
- Low Flow

Showers

Electric Water Heaters

SHC saves space

The SHC mini tank frees up precious space while providing plenty of hot water for hand washing or kitchen type applications. Why store 30 or more Gallons of hot water when 4 Gallons are sufficient for the job?

SHC saves water and electricity

By putting the hot water right where it is needed, you can reduce pipe runs from a central hot water tank. This reduces the use of water and energy. The smaller tank coupled with good insulation also reduces the stand-by losses in comparison with larger tank type water heaters.

Installation is quick

The unit installs right under or near the sink. Lightweight and compact, the SHC mounts to the wall (bracket included). Once it is filled with water, simply plug it into a 110-120V outlet. With only a 10 amp. current draw, no special wiring is required.

Quality product

Stiebel Eltron is known for high quality products the SHC is no exception. The unit offers a six year warranty on the tank, two years on the other components.

Technical Specifications

Model		
Phase		1
Voltage	V	110 -120
Wattage	W	1200
Amperage	A	11
Nominal Water Volume	Gal / L	3.96 / 15
Weight Empty	Lbs / kg	22 / 10
Height	Inch / cm	18.19 / 46.2
Width	Inch / cm	12.28 / 31.2
Depth	Inch / cm	12.28 / 31.2
Maximum Operating	PSI / Bar	150 / 10
Pressure		
Maximum Adjustable	°F / °C	171° / 77°
Temperature		
Recovery Time	Minutes	60
Water Connections		1/2" NPT

Distributed by:

STIEBEL ELTRON, Inc.

242 Suffolk Street, Holyoke, MA 01040 Phone: (413) 538-7850 • (800) 582-8423

Fax: (413) 538-8555

E-mail: info@stiebel-eltron-usa.com

Please visit our web site at www.stiebel-eltron-usa.com