



Product Name & Number:	Kingsmill – WEK 11 32251
Collection:	Artiquity
Construction:	Engineered
Face Species:	Elm (Ulmus)
Core Species:	Poplar
Number of Plies:	9
Thickness:	1/2"
Width:	5"
Grade:	Standard
Profile:	Kissed Edges/Kissed Ends
Face Finish:	Smooth
Finish Treatment:	Matte Aluminum Oxide
Gloss Level:	10° + or - 5°
Sq. Ft. per Carton:	19.69
Sq. Ft. per Pallet:	1,023.88
Cartons per Pallet:	52
Weight per Carton:	35.42 lbs
Weight per Pallet:	1,841.84 lbs
Installation:	Glue Down/Nail/Staple/Float On/Above Grade Woor/Concrete
Warranties:	25 year Finish Lifetime Structure Lifetime Moisture
Certifications	Floor Score Forest Stewardship Council FSC Number SCS-COC-003140 Carb Phase 2 compliant
Smoke Density:	Under 450
Janka Hardness:	860
Photo Sensitivity:	2
Character Variation:	Low
Sound Transmission (STC):	
MoistureGuard:	54
SilentGuard:	54
Impact Insulation Class (IIC):	
MoistureGuard:	59
SilentGuard:	59

PRODUCT SPEC SHEET



Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

Janka Wood Hardness Scale is a good indicator of a wood species' resistance to indentations, however all wood will dent and scratch.

3-11-11 Update

Color	Quarter Round		Reducer		Baby Threshold		T-Molding		Stair Noising Wood Filler		Wood Filler	
Antique Elm	HQRTA	05027	HREDD	05027	HENDD	05027	HTMDA	05027	HSFTD	05027	WF	650

PRODUCT SPEC SHEET