

VT65MLMED



33.5" x 23.63" x 23.5" (H x W x D)

24" wide all-freezer for freestanding use capable of -25° C operation; includes audible alarm, lock, and hospital grade plug

Highlights:

-25° C operation for safe storage of temperature sensitive materials

Includes a hospital grade cord with a 'green dot' plug

High temperature alarm includes external temperature readout

Product Features:

-25°C capable	Low temperature capability ideal for certain sensitive items
Factory installed lock	Keyed lock for secure interior
High temperature alarm	Warns of temperature fluctuations and includes an external temperature readout on the door
Hospital grade cord with 'green dot' plug	Secure three-pronged cord for added unit safety
Manual defrost	Efficient performance with reliable temperature stability
Pull-out drawers	Clear baskets for convenient and separated storage
Access port	Unit comes with a factory installed probe hole for users to connect their own monitoring equipment
Adjustable thermostat	Manage the temperature with ease and accuracy
Fully finished white cabinet	Allows the unit to be used freestanding

VT65MLMED Specifications:

Overview	
Height of Cabinet	33.5" (85 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	25.13" (64 cm)
Depth with door at 90°	46.13" (117 cm)
Capacity	3.2 cu.ft. (91 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Amps	1.3
Shipping Weight	102.0 lbs. (46 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	24.25" (62 cm)
Interior Width	17.75" (45 cm)
Interior Depth	16.5" (42 cm)
Thermostat Type	Dial
Refrigerant Type	R134a
Refrigerant Amount	2.7 oz.
High Side PSI	235.0
Low Side PSI	70.0
Level Legs	2
Interior Drawers	Yes
Drawers Qty	3
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	17.5" (44 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	-20°C to -30°C

