

## **FOCUS106**



30.75" x 41.63" x 25.88" (H x W x D)

Curved top commercial ice cream freezer with sliding glass lid, digital thermostat, novelty baskets, and 9.5 cu.ft. interior

## **Highlights:**

Angled top helps to provide easier product visibility to maximize impulse sales

Digital controls offer easy and intuitive temperature management

Baskets included for convenient storage

## **Product Features:**

Commercially approved	UL-S listed to NSF-7 Standards for use in commercial establishments
Digital thermostat	Electronic controls for more precise temperature management
Wide temperature range	Digital thermostat can be set between -13 and +23°F to accommodate a variety of frozen treats
Baskets included	Three epoxy-coated wire baskets included to store novelty items
Angled top	Curved design makes it easier for customers to view interior contents
Strong insulation	3" thick insulation helps to ensure items stay cold
Manual defrost	Static cooling system for improved temperature stability
Sliding glass lid	Two tempered glass lids on ball-bearing glides slide open and closed easily for added efficiency
Removable lock	A keyed lock is included for optional use





## **FOCUS106 Specifications:**

Canadian Electrical Safety  Sanitation  UL  Amps  7  Voltage/Frequency  115 V AC/60 II	m) L) ual uss ite UL LC 7.2
Depth 25.88" (66 cm) Capacity 9.5 cu.ft. (269 Defrost Type Manual Door Glate What US Electrical Safety Canadian Electrical Safety Sanitation UL Amps 7 Voltage/Frequency 115 V AC/60 II	m) L) ual uss iite UL LC -S
Capacity 9.5 cu.ft. (269  Defrost Type Manu  Door Gla  Cabinet Wh  US Electrical Safety Canadian Electrical Safety Sanitation UL  Amps 7  Voltage/Frequency 115 V AC/60 II	L)  Jual  Just Site  JL  LC  7.2
Defrost Type Manu Door Gla Cabinet Wh  US Electrical Safety Canadian Electrical Safety Sanitation UL  Amps 7  Voltage/Frequency 115 V AC/60 I	ite UL LC
Door Gla Cabinet Wh US Electrical Safety US Sanitation UL Amps 7 Voltage/Frequency 115 V AC/60 I	ite UL LCS
Cabinet Wh US Electrical Safety US Canadian Electrical Safety Sanitation UL Amps 7 Voltage/Frequency 115 V AC/60 I	ite UL LC -S 7.2
US Electrical Safety  Canadian Electrical Safety  Sanitation  UL  Amps  7  Voltage/Frequency  115 V AC/60 I	UL LC S
Canadian Electrical Safety  Sanitation  UL  Amps  7  Voltage/Frequency  115 V AC/60 I	LC S 7.2
Safety Sanitation UL Amps 7 Voltage/Frequency 115 V AC/60 I	S 7.2
Amps 7 Voltage/Frequency 115 V AC/60 I	7.2
Voltage/Frequency 115 V AC/60 I	
	Hz
Weight 120.0 lbs. (54 k	— (g)
Shipping Weight 125.0 lbs. (57 kg	 (g)
Parts & Labor Warranty 1 Ye	ar
Compressor Warranty 5 Year	ars
UPC 7611010602	17
Freezer	
Door Swing Slidi	ng
Interior Height 20.75" (53 cm	m)
Interior Width 35.5" (90 cm	m)
Interior Depth 19.63" (50 cm	m)
Thermostat Type Digi	tal
Refrigerant Type R29	— 0а
Refrigerant Amount 3.0 c	oz.
High Side PSI 345	5.0
Low Side PSI 140	0.0
Compressor Step Height 9.75" (25 cm	m)
Compressor Step Width 7.88" (20 cm	m)
Compressor Step Depth 19.63" (50 cm	m)
Temperature Range -13 to 23	°F

