

SPECIFICATIONS BFQ140 EXHAUST FANS

120 CFM/4.0 SONES @ 0.10" WG. HVI CERTIFIED 120 Volts, 0.75 amps, 60 hz.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10" x 10".

Blower Wheel

One piece polymeric wheel 51/8" diameter, 23/8" wide, with 48 fins.

Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz., 0.75 amps.

Fan Housing

Flame retardant ABS, 0.110" thick, dimensions 81/2" x 91/16" x 43/4".

Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area

For bathrooms up to 120 sq. ft. For other rooms up to 145 sq. ft.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

Unit Mounting

Rated for ceilings insulated to R-40. Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to 3 /4", with a rough-in opening of 8^{1} /2" x 9^{1} /16".

Single Pack Shipping Info

Box Dim: 11" x 12" x 6" UPC: 0-8316221401-0 Shipping Weight: 5¹/4 lbs.

PERFORMANCE											
									HVI Sones	Fan Speed	Power
	Static Pressure (inches of w.g.)								@ .1 SP	RPM	Watts
	0	0.05	0.1	0.125	0.15	0.2	0.25	0.3			
Air Flow - CFM	129	124	120	117	115	109	102	93	4.0	1525	68

PROJECT	PROJECT							ARCHITECT					
LOCATION							ENGINEER						
CONTRACTOR							SUBMITTED BY DATE						
FAN MODEL NUMBER NUMBER	СҒМ	IN W.G.	RPM	WATTS	AMPS	SONES	ΩТΥ	OPTIONAL EQUIPMENT & REMARKS					





U.S.: 820 Lincoln Drive West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785 Fax: (610) 696-8048

Tel: (905) 456-2033 Fax: (905) 456-1015

Canada: 110 Glidden Road

Brampton, Ontario L6T 2J3