




Description:

The Rainbow I Down pendant with two glass shades, inner cased glass is frosted white. Outer glass is clear with a dichroic coating or with colored glass. The dichroic coated glass has a liquid mercury-like finish when off but when lit will show a fusion of dichroic colors. Uni-plug design allows the Rainbow I Down pendant to be mounted on any lighting system or ceiling canopy through the use of an appropriate adaptor, not included. Standard cable length of 59" can be field-cut or specified when ordering. May be specified with Kiss canopy by adding /MP to part number or /MP2 for 2" version.

Part Numbers:

- | | |
|-----------------|--------------------------------------|
| 220721bz | bronze, orange glass |
| 220721ch | chrome, orange glass |
| 220721mc | matte chrome, orange glass |
| 220722bz | bronze, smoky glass |
| 220722ch | chrome, smoky glass |
| 220722mc | matte chrome, smoky glass |
| 220723bz | bronze, turquoise glass |
| 220723ch | chrome, turquoise glass |
| 220723mc | matte chrome, turquoise glass |
| 220724bz | bronze, red glass |
| 220724ch | chrome, red glass |
| 220724mc | matte chrome, red glass |
| 220913bz | bronze, dichroic rainbow glass |
| 220913ch | chrome, dichroic rainbow glass |
| 220913mc | matte chrome, dichroic rainbow glass |
| 220918bz | bronze, dichroic sunrise glass |
| 220918ch | chrome, dichroic sunrise glass |
| 220918mc | matte chrome, dichroic sunrise glass |



Technical Specs:

- 12V AC/DC input
- 50VA, 50W for 1 (maximum 50 Watt lamp)
- GY6.35 socket
- Suitable for dry locations only
- Dimmable