



### Description:

The Rainbow II wall sconce may be mounted as an up-light or a down-light. The wall sconce may be mounted as a square or at an 45 degree angle to create a diamond shape. The metal canopy and stem is available in bronze. A 75W dimmable electronic transformer is included on the mounting plate.

### Part Numbers:

|                 |                                      |
|-----------------|--------------------------------------|
| <b>101725bz</b> | bronze, orange glass                 |
| <b>101725ch</b> | chrome, orange glass                 |
| <b>101725mc</b> | matte chrome, orange glass           |
| <b>101726bz</b> | bronze, smoky glass                  |
| <b>101726ch</b> | chrome, smoky glass                  |
| <b>101726mc</b> | matte chrome, smoky glass            |
| <b>101728bz</b> | bronze, turquoise glass              |
| <b>101728ch</b> | chrome, turquoise glass              |
| <b>101728mc</b> | matte chrome, turquoise glass        |
| <b>101729bz</b> | bronze, red glass                    |
| <b>101729ch</b> | chrome, red glass                    |
| <b>101729mc</b> | matte chrome, red glass              |
| <b>101816bz</b> | bronze, retro white glass            |
| <b>101816ch</b> | chrome, retro white glass            |
| <b>101816mc</b> | matte chrome, retro white glass      |
| <b>101817bz</b> | bronze, retro black glass            |
| <b>101817ch</b> | chrome, retro black glass            |
| <b>101817mc</b> | matte chrome, retro black glass      |
| <b>101916bz</b> | bronze, dichroic rainbow glass       |
| <b>101918ch</b> | chrome, dichroic rainbow glass       |
| <b>101918mc</b> | matte chrome, dichroic rainbow glass |
| <b>101919bz</b> | bronze, dichroic sunrise glass       |
| <b>101919ch</b> | chrome, dichroic sunrise glass       |
| <b>101919mc</b> | matte chrome, dichroic sunrise glass |

### Technical Specs:

120V AC, 50/60Hz input  
 11.7V AC output  
 50VA, 49W for 1(maximum 50 Watt lamp)  
 GY6.35 socket  
 Suitable for dry locations only  
 Mount to 3 1/2" - 4" round J-box

Short circuit protection  
Overload protection  
Thermal protection  
Dimmable