


INSTALLATION INSTRUCTIONS

USA

LINE VOLTAGE PENDANT

SIERRA 120

ART. NO. 110 114bz/CF/MP	bronze, compact fluorescent, amber glass wire mesh
110 114bz/IN/MP	bronze, incandescent, amber glass wire mesh
110 114ch/CF/MP	matte chrome, compact fluorescent, amber glass wire mesh
110 114ch/IN/MP	matte chrome, incandescent, amber glass wire mesh



IMPORTANT SAFETY INSTRUCTIONS



1. Read all instructions!
2. Turn off power prior to any work on the canopy.
3. THIS PRODUCT MUST BE INSTALLED BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED, IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE.
4. This LINE VOLTAGE PENDANT MUST BE HARD WIRED, 120v. For all the wire connections, use Listed Wire Nuts.
5. Warranty is void in case of unauthorized modifications and/ or improper use.

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THE SYSTEM

This Package Contains: SIERRA 120 - qty.(1)

- Insert screw (A) into the mounting plate (B).
Align screws (A) with the J-box and tighten until
firmly connected.

- There are markings on the cable wire (C)
showing; L is for Line Voltage, N is for the Neutral
Connection, and G is for the Ground Connection.

**Warning! If cutting cable wire make note which
side is L, N, and G.**

- Adjust the cable length (C) by loosening the
center cable lock (D).

- Place the canopy cover (E) over the mounting
plate (B) and secure it with the allen screw (F)
located on the side of the base.

