



Description:

The Rainbow II CM comes with two glass shades, the inner cased glass is frosted white. The outer glass can be clear with a dichroic coating or with colored glass. The dichroic coated glass has a liquid mercury-like finish when off but when lit will show a fusion of dichroic colors. The Rainbow II CM includes a 4" ceiling mount canopy with 75 Watt transformer. Rainbow with 2" ceiling mount canopy available.

Part Numbers:

- 131725bz/CM** bronze, orange glass
- 131725ch/CM** chrome, orange glass
- 131725mc/CM** matte chrome, orange glass
- 131726bz/CM** bronze, smoky glass
- 131726ch/CM** chrome, smoky glass
- 131726mc/CM** matte chrome, smoky glass
- 131728bz/CM** bronze, turquoise glass
- 131728ch/CM** chrome, turquoise glass
- 131728mc/CM** matte chrome, turquoise glass
- 131729bz/CM** bronze, red glass
- 131729ch/CM** chrome, red glass
- 131729mc/CM** matte chrome, red glass
- 131816bz/CM** bronze, retro white glass
- 131816ch/CM** chrome, retro white glass
- 131816mc/CM** matte chrome, retro white glass
- 131817bz/CM** bronze, retro black glass
- 131817ch/CM** chrome, retro black glass
- 131817mc/CM** matte chrome, retro black glass
- 131916bz/CM** bronze, dichroic rainbow glass
- 131916ch/CM** chrome, dichroic rainbow glass
- 131916mc/CM** matte chrome, dichroic rainbow glass
- 131919bz/CM** bronze, dichroic sunrise glass
- 131919ch/CM** chrome, dichroic sunrise glass
- 131919mc/CM** matte chrome, dichroic sunrise glass

Technical Specs:

120V AC, 50/60Hz input
 11.7V AC output
 50VA, 49W for 1(maximum 50 Watt lamp)
 GY6.35 socket

Suitable for dry locations only
Mount to 3 1/2" - 4" round J-box
Short circuit protection
Overload protection
Thermal protection
Dimmable