

120V LED/INCANDESCENT ACCENT

LARGE



AZT

BKT

15251 AZT, BKT

SMALL COMPACT



AZT

15230 AZT

Ordering Guide & Finish	15251 AZT, BKT	15230 AZT
Housing	Cast Aluminum. Tempered convex glass lens.	Textured Architectural Bronze
Lamp Base	4000V (4KV) pulse rated medium base porcelain socket	4000V (4KV) pulse rated medium base porcelain socket
Supplied Lamp	Lamp not supplied unless noted	Lamp not supplied unless noted
Incandescent Lamp Options	175-W Max. PAR38 Metal Halide, 100-W Max. E17 Metal Halide or 150-W Max. PAR38/R40 Incandescent Reflector: for use with E17 lamp. Removable for PAR38/R40 use.	35-W Max. PAR20 Metal Halide or 50-W Max. PAR20 Incandescent
LED Lamp Options	17W PAR38 Wet (18093-18098) see page 166. Compares up to 75W Halogen.	N/A
Wiring	8" of usable 200°C 18 AWG wire leads	8" of usable 200°C 18 AWG wire leads
Optional Mounting Access.	15276 – Power Post® 15601 – Surface Mounting Flange, for attachment to junction box (not included) 15609 – Junction Box Mounting Bracket	15276 – Power Post® 15601 – Surface Mounting Flange, for attachment to junction box (not included) 15609 – Junction Box Mounting Bracket
Optional Lens Accessories	15660 – Medium Cowl 15668 – Long Cowl 15625 – Blue Filter 15639 – Hexcell Louver	15630 – Cowl with glass lens
Notes	Accents require remote ballasts for High Intensity Discharge. See HID Ballast Guide on page 159 and 120V Lamp Guide on page 166. For Lamp Photometrics see page 169.	Accents require remote ballasts for High Intensity Discharge. See HID Ballast Guide on page 159 and 120V Lamp Guide on page 166. For Lamp Photometrics see page 169.