

LAFAYETTE™  
LANTERN



TZG

15313 TZG

LARKIN  
ESTATE™



OZ

15444 OZ

Ordering Guide & Finish	15313 TZG	15444 OZ																																								
Housing	Cast Aluminum with linen seeded glass	Cast Brass with umber etched glass																																								
Lamp Base	12V T5 wedge base socket	12V S8 wedge base socket																																								
Supplied Lamp	16.25-W(VA) 912X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)																																								
Incandescent Lamp Options	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	18.5-W(VA) 3155K (15599CLR)																																								
LED Lamp Options	2W (18039-18041) see page 137. Compares up to 16W Xenon.	2W (18039-18041) see page 137. Compares up to 16W Xenon.																																								
Wiring	35" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	40" of usable #18-2, SPT-1-W leads. Cable connectors supplied.																																								
Mounting Access. (Included)	8" In-ground slotted stake	8" In-ground slotted stake																																								
Optional Accessories	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket																																								
Notes	U.S. Patent Pending	Brass will develop natural patina over time																																								
Photometric with Supplied Lamp	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Foot Candles</td> <td>1.3</td> <td>3</td> <td>1.96</td> <td>.86</td> <td>.33</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Foot Candles	1.3	3	1.96	.86	.33	-	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Foot Candles</td> <td>10.8</td> <td>6.9</td> <td>0.7</td> <td>0.4</td> <td>0.2</td> <td>0.1</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Foot Candles	10.8	6.9	0.7	0.4	0.2	0.1	-	-	-
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Foot Candles	1.3	3	1.96	.86	.33	-	-	-	-																																	
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Foot Candles	10.8	6.9	0.7	0.4	0.2	0.1	-	-	-																																	