


ADJUSTABLE
UNDER RAILING




Wall mount



AZT

LOUVERED
DOWN



BKT



WHT

15077 AZT

15066 AZT, WHT

Ordering Guide & Finish	15077 AZT	15066 AZT, WHT																		
Housing	Aluminum	Aluminum																		
Lamp Base	12V S8 wedge base socket	12V T5 wedge base socket																		
Supplied Lamp	18.5-W(VA) 3155K (15599 CLR) Krypton light source Power usage at 12V AC input VA MAX: 18.5-W(VA)	6.5-W(VA) 918X (17022) Xenon light source Power usage at 12V AC input VA MAX: 6.5-W(VA)																		
Incandescent Lamp Options	N/A	4-W(VA) 901X (17021)																		
LED Lamp Options	2W (18036-18038) see page 137. Compares up to 18.5W Krypton.	N/A																		
Wiring	72" of usable #18-2, SPT-1-W leads. Cable connectors supplied.	72" of usable #18-2, SPT-1-W leads. Cable connectors supplied.																		
Mounting Access. (Included)	Mounting hardware	Stainless Steel mounting plate																		
Notes	N/A	U.S. Patent No. D437,445																		
Photometric with Supplied Lamp	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'	Mounting Height	.5'	1'	1.5'	2'	2.5'	3'	3.5'	4'	
	Foot Candles	4.7	3.1	1.5	.35	.15	.08	-	-	-	6'	5.2	.4	-	-	-	-	-	-	-
											12'	19	.6	.1	-	-	-	-	-	-
											30'	2.4	.2	.1	-	-	-	-	-	-