

MR-16 MINI
(DOWN)



15093 WHT

LONG COWL
MINI



15494 AZT

	15093 WHT	15494 AZT
Ordering Guide & Finish	15093 WHT	15494 AZT
Housing	Cast Aluminum with stainless steel screen	Cast Aluminum. Heat-resistant flat glass lens is fully sealed.
Lamp Base	12V Incandescent bi-pin, high temperature porcelain socket	12V Incandescent bi-pin, high temperature porcelain socket
Supplied Lamp	Lamp not supplied unless noted	Lamp not supplied unless noted
Incandescent Lamp Options	Power usage at 12V AC input VA MAX: 50-W(VA) MR-16 20-W(VA) Max. Canada 35-W(VA) MR-11 see page 140	Power usage at 12V AC input VA MAX: 50-W(VA) MR-16 20-W(VA) Max. Canada 35-W(VA) MR-11 see page 140
LED Lamp Options	4W (18126-18133) see page 137 Compares to 20W Halogen 5W (18134-18141) see page 137 Compares to 35W Halogen	4W (18126-18133) see page 137 Compares to 20W Halogen 5W (18134-18141) see page 137 Compares to 35W Halogen
Wiring	35" of usable #18-2, SPT-1-W leads. Cable connectors supplied. 12V porcelain universal bi-pin socket.	35" of usable #18-2, SPT-1-W leads. Cable connectors supplied.
Mounting Access. (Included)	15607 – White Surface Mounting Bracket and Hardware	15609 – Junction Box Mounting Bracket
Optional Mounting Accessories	N/A	15601 – Surface Mounting Flange 15607 – Surface Mounting Bracket 15609 – Junction Box Mounting Bracket 15647 – 90° Elbow 15649 – Stem Coupler 15645, 15656, 15657, 15658 or 15570 – Stems
Optional Lens Accessories	N/A	15675 LIN – Linear Lens 15676 FRO – Frosted Lens 15679 BK – Louver 15686 BL – Blue Filter
Notes	See page 175 for photometrics. For downlight use only.	See page 175 for photometrics