

Lighting Your Life Since 1970

Product Specifications - 40291WGET			
Job Name: Job Type:			
Quantity:	Comments		



40291WGET

Morrow Bay VX 3-Light Outdoor Hanging Lantern

Finish Earth Tone

Lamping

Number of Bulbs	3	Width
Light Type	Incandescent	Height
Bulb Type	CA	Length
Max Bulb Wattage	60	Extension
Max Fixture Wattage	180	Back Plate Wid
Rated Life	±1,500 Hours	Back Plate Heig
Rated Lumens	±2,016	HCO
Color Temp	±2,700 K	Min Overall Hei
Bulb(s)	Not Included	Max Overall He
Light Up/Down	N/A	Hanging Weigh
Beam Spread	N/A	Height Adjusta
CRI	N/A	Slope
Photo Cell Included	N/A	Chain Length
Ballast/Driver/Transformer	No	Wire Length
Dimmable	Standard Dimmer	Canopy Width

Glass/Shade
147 1 01

Measurements

Canopy Height

Canopy Length

Other

Width	10.5"
Height	21.5"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	7.0 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	72"
Wire Length	144"
Canopy Width	N/A

Product Category

Outdoor Hanging Lantern

Sh	ipį	oir	ıg	
Ca	rtc	'n	W	۵

7.0 lbs
13'
14'
27'
2.64
1
N/A
Yes

	rtificati	on				
--	-----------	----	--	--	--	--

Cerunication		Other	
Safety Rating	Wet	UPC Code	783209063433
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Vivex

IIVa	

N/A

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.