

Lighting Your Life Since 1970

Product Specifications - 6503CLCS			
Job Name:	Job Type:		
Quantity:	Comments		



6503CLCS

3-Light Flush Mount

Finish Country Stone

Number of Bulbs

Lamping

Dimmable

Light Type Incandescent **Bulb Type** CA Max Bulb Wattage 25 Max Fixture Wattage **Rated Life Rated Lumens Color Temp** Bulb(s)

75 ±2,500 Hours ±636 ±2,700 K Not Included Light Up/Down N/A **Beam Spread** N/A N/A **Photo Cell Included** N/A Ballast/Driver/Transformer No

Glass/Shade Clear

Measurements

Canopy Height Canopy Length

3

Standard Dimmer

Width 9.5" Height 6.0" Length N/A Extension N/A **Back Plate Width** N/A **Back Plate Height** N/A HCO N/A Min Overall Height N/A Max Overall Height N/A **Hanging Weight** 2.6 lbs **Height Adjustable** N/A Slope N/A **Chain Length** N/A Wire Length N/A **Canopy Width** N/A **Product Category**

Flush Mount

Shinning

Snipping	
Carton Weight	2.6 lbs
Carton Width	10'
Carton Height	7'
Carton Length	10'
Carton Cubic Feet	0.41
Master Pack	4
Master Pack Weight	16.5 lbs
Master Pack Width	10.9'
Master Pack Height	15.3'
Master Pack Length	20.5'
Master Cubic Feet	1.97
UPS Shippable	Yes

Certification

Dry UPC Code **Safety Rating Energy Star** No **Shades Included** CA Title 24 Crystals Included No CA Title 20 No Diffuser Included **ADA** Conversion Kit No Dark Sky N/A Material

Other	Equivalent

N/A

N/A

	Lyuivaieiits	
783209650329	Incandescent Watts	N/A
N/A	Fluorescent Watts	N/A
N/A		
N/A		
N/A		
Copper		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.