

## Lighting Your Life Since 1970

Product Specifications - 87802WT				
Job Name:	Job Type:			
Quantity:	Comments			

## 87802WT

CounterMax MX-FS 35" 1-Light Fluorescent Kit

<b>Finish</b> White		Glass/Shade		<b>Product Category</b> Under Cabinet	
Lamping		Measurements	0.01	Shipping	0.0 !!
Number of Bulbs	1	Width	3.3"	Carton Weight	2.0 lbs
Light Type		Height	1.0"	Carton Width	3"
Bulb Type	Mini Bi Pin T5	Length	35.0"	Carton Height	2"
Max Bulb Wattage	21	Extension	N/A	Carton Length	38"
Max Fixture Wattage	21	Back Plate Width	N/A	Carton Cubic Feet	0.11
Rated Life		Back Plate Height	N/A	Master Pack	3
Rated Lumens	±2,100		N/A	Master Pack Weight	11.0 lbs
Color Temp	±3,100 K	Min Overall Height	N/A	Master Pack Width	5.5"
Bulb(s)	Included	Max Overall Height	N/A	Master Pack Height	5.5"
Light Up/Down	N/A	Hanging Weight	2.0 lbs	Master Pack Length	41.1"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	0.72
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	Yes	Wire Length	N/A		
Dimmable	N/A	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		
		canopy Longin	1471		
Certification		Other		Equivalents	
UL Standard	Dry	UPC Code	783209015685	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Acrylic		
Dain Sky	IN/A	material	Actylic		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.