

INSTALLATION INSTRUCTIONS

Item#770 (New. 11/29/2011)

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

ASSEMBLING THE FIXTURE (Fig.1)

1. Shut off the power at the circuit breaker (**avertissement! couper le courant au niveau des fusibles ou du disjoncteur**) and remove the old fixture from the ceiling, including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for the installation.
3. Attach the crossbar (A) to the outlet box using the two screws (C). The side of the crossbar (A) marked "GND" must face out.
4. Place the glass shade (J), plastic washer (M) and metal washer (L) onto the nipple that located on the center of fixture body (H), then secure with cap nut (K).
5. Adjust the arms (F) to the proper position, then secure them to the fixture body (H) with ball nut (G). Secure the finial (I) to the nipple on the bottom end of fixture body (H).
6. Hang the crystal drops (N) on the front edge of the metal leaves on the arms (F).

CONNECTING THE WIRES (Fig. 2)

7. At this point, connect the electrical wire as shown in figure 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixtures ground wire to it. Otherwise, connect the fixture ground wire directly to the crossbar using the green screw provided.

COMPLETING THE INSTALLATION (Fig. 1)

8. Secure the canopy (D) by thread studs (B) 1/4" into the pre-drilled holes in the crossbar (A) spaced at the same distances apart as the holes in the canopy (D).
9. Carefully lift the canopy (D) and insert the studs (B) through the pre-drilled holes into threading studs (B). Secure canopy against ceiling with knurled knobs (E).
10. Install the bulb(s) (not included) in accordance with the fixture's specification. (**DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**) (**NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!**)

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

