



Job Name:

Job Type:

Comments:

Quantity:

Product Number: 11018

Dimensions:



Diameter: 7 3/16"

Switch Type: N/A

Length: 13 15/16"

Mounting Proc.: Other

Height: 8 7/16"

Bulbs:

- 1 - Medium Par30S 50w max 120v - Not included
- 1 - Medium Par30 75w max 120v - Not included
- 1 - Medium Par38 90w max 120v - Not included
- 1 - Medium BR-30 65w max 120v - Not included
- 1 - Medium BR-40 90w max 120v - Not included
- 1 - Medium Par30L 75w max 120v - Not included
- 1 - Medium BR-30 65w max 120v - Not included
- 1 - Medium Par30S 50w max 120v - Not included
- 1 - Medium Par30L 75w max 120v - Not included
- 1 - Medium Par38 90w max 120v - Not included
- 1 - Medium BR-30 65w max 120v - Not included
- 1 - Medium BR-40 90w max 120v - Not included
- 1 - Medium Par30L 75w max 120v - Not included
- 1 - Medium BR-30 65w max 120v - Not included
- 1 - Medium Par30L 75w max 120v - Not included
- 1 - Medium BR-30 65w max 120v - Not included
- 1 - Medium A-19 40w max 120v - Not included
- 1 - Medium Par30S 50w max 120v - Not included
- 1 - Medium Par30L 75w max 120v - Not included
- 1 - Medium Par38 90w max 120v - Not included
- 1 - Medium A-19 40w max 120v - Not included
- 1 - Medium A-19 40w max 120v - Not included
- 1 - Medium A-19 40w max 120v - Not included
- 1 - Medium A-19 40w max 120v - Not included

Material List:

- 1 Housing - Steel - Raw Steel

Safety Listing:

- cUL Listed for Damp Locations / IC
- UL Listed for Damp Locations / IC

Instruction Sheets

- English (HC-1343)

11018 - Remodel IC Airtight Housing

Remodel IC Airtight 6" Housing

Trims: 11032AT, 11037AT, 11038AT, 11045AT, 11020AT, 11033AT, 11034AT, 11035AT, 1136AT, 11039IT, 1151AT, 1154AT, 11055AT

Safe- Thermally Protected/Listed for Damp Location: IC housing is approved for use in direct contact with insulation.

Easy Access Housing: Housing removable for easy access to junction box.

Sealed Trim: One piece sealed trims. No light leaks.

Snap-In Socket: Snap in socket locates lamp in optimum position.

Time-Saving Junction Box Design: Junction box saves installation time with snap-on covers, pry-out knock-outs, riveted ground wire, and through-circuit wiring, with 2-in, 2-out #12 wire.

Easy Installation: Provided with mounting clips for fast, easy installation.

Airtight Construction: Meets airtight requirements for 2.0 CFM or less air leakage.

UPC #: 785652110184

Product Type: Recessed Light

Features:

Title 24

Trim



11020AT-15

6" Open Trim

White Steel Trim
 Maximum Wattage:
 75w Par30L
 65w BR-30



11032AT-14

6" Multiplier Trim

White Trim / Baffle
 Aluminum Trim
 Maximum Wattage:
 75w Par30
 90w Par38
 65w BR-30
 90w BR-40
 50w Par30S



11032AT-172

6" Multiplier Trim

Antique Bronze Aluminum
 Aluminum Multiplier
 White Aluminum Trim
 Maximum Wattage:
 75w Par30
 90w Par38
 65w BR-30
 90w BR-40
 50w Par30S



11032AT-22

6" Multiplier Trim

Polished Aluminum Aluminum
 Aluminum Multiplier
 White Aluminum Trim
 Maximum Wattage:
 75w Par30
 90w Par38
 65w BR-30
 90w BR-40
 50w Par30S



11032AT-71

6" Multiplier Trim

Antique Bronze Aluminum
 Aluminum Multiplier
 Antique Bronze Aluminum Trim
 Maximum Wattage:
 75w Par30
 90w Par38
 65w BR-30
 90w BR-40
 50w Par30S



11032AT-849

6" Multiplier Trim

Satin Nickel Aluminum
 Trim
 Maximum Wattage:
 75w Par30
 90w Par38
 65w BR-30
 90w BR-40
 50w Par30S



11032AT-861

6" Multiplier Trim

Satin Nickel - White Aluminum
 Aluminum Multiplier
 White Aluminum Trim
 Maximum Wattage:
 75w Par30
 90w Par38
 65w BR-30
 90w BR-40
 50w Par30S



11033AT-15

6" Flat Glass Shower Trim

Satin White Glass Diffuser
 White Aluminum Reflector
 White Aluminum Trim
 Maximum Wattage:
 40w A-19
 Suitable For Shower Light



11034AT-15

6" Drop Lens Shower Trim

Satin White Glass Diffuser
 White Aluminum Reflector
 White Aluminum Trim
 Maximum Wattage:
 40w A-19
 Suitable For Shower Light



11035AT-15

6" Flat Glass Trim

Satin White Glass Diffuser
 White Aluminum Reflector
 White Steel Trim
 Maximum Wattage:
 40w A-19
 Suitable For Shower Light



11037AT-15

6" Regressed Eyeball Trim

White
 White Steel Trim
 Maximum Wattage:
 75w Par30L
 65w BR-30



11039AT-15

6" Wall Wash Trim

White Steel Housing
 White Steel Trim
 Maximum Wattage:
 40w A-19



11055AT-15

6" Fresnal Glass Shower T

Clear Glass Glass
 White Aluminum Reflector



1136AT-15

6" Eyeball Trim

White
 White Steel Trim



1151AT-14

6" Baffle Trim

White Trim / Baffle Aluminum
 Trim



1151AT-15

6" Baffle Trim

Black Aluminum Baffle
 White Aluminum Trim

White Aluminum Trim
 Maximum Wattage:
 40w A-19
 Suitable For Shower Light

Maximum Wattage:
 75w Par30L
 65w BR-30

Maximum Wattage:
 75w Par30L
 90w Par38
 65w BR-30
 90w BR-40
 50w Par30S

Maximum Wattage:
 75w Par30L
 90w Par38
 65w BR-30
 90w BR-40
 50w Par30S



1154AT-14

6" Open Cone Shower Trim

White Trim / Baffle Aluminum
 Baffle
 White Trim / Baffle Aluminum
 Trim
 Maximum Wattage:
 50w Par30S
 75w Par30L
 90w Par38
 Suitable For Shower Light

Shipping Information

Package Type	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship	Label
Individual	1	785652110184	21	7	8	0.681	1.5	Yes	C IP-3
Master Pack	6	10785652110181	21.5	20.5	9	2.296	11.5	Yes	A M-1