

# The TH110

## Electronic Programmable Thermostat

PHONE 360.693.2505  
 FAX 360.694.8668  
 WEB [www.cadetco.com](http://www.cadetco.com)



**CADET**<sup>®</sup>  
 SAFETY & QUALITY



### Best Choice Programmable

### Features and Benefits

- Advanced temperature control ensures comfort by minimizing temperature swings to  $\pm 0.5^{\circ}\text{C}/0.9^{\circ}\text{F}$
- Use with 240 or 208 Volt In-Wall Electric Heaters and Baseboards, up to 3840 watts
- Large, legible LCD display in slim profile design
- Zero crossover contact relay minimizes noise
- 7-day programming with Early Start Function, 4 daily time periods and pre-programmed or personalized schedule
- Push button programming override options
- On/Standby switch enables positive thermostat shutdown for added security
- Double pole (4 wires)

#### General Information:

Save up to 28% on your heating bill with the TH110-DP-P programmable electronic thermostat. The TH110 provides constant comfort with digital temperature sensing and control, and can suit all needs with a choice of easy push button 7-day personalized or pre-programmed settings. The large, legible LCD makes this a premium choice in a programmable thermostat. This double pole (4 wire) model thermostat is recommended for both 240 and 208 volt (line voltage) baseboard and in-wall fan heaters. Setpoint range: 40°F to 86°F (5°C to 30°C).

**Ordering Information:** Available in white.

#### Architectural Information:

The electronic thermostat shall be UL and CSA Listed. The line voltage temperature control shall be digital with LCD display. Switching means shall be by "zero crossover" to minimize RF line noise. The control shall be capable of switching loads of 16 amps at 240 VAC. LCD display shall show time of day, actual room temperature, mode and current status of the heater. Programming choices shall be 7-day with 4 daily settings. Unit shall have programmed a default temperature of 62°F (16.5°C). Device shall have ability to retain programming indefinitely. No batteries shall be required for operation.

TH110-DP-P

### Carton Details

#### Product

**DIMENSIONS** | 3"W x 5.1"H x 1.6"D

#### Package

**DIMENSIONS** | 7.25"W x 8.75"H x 2"D

**Carton** (6 units per carton)

**DIMENSIONS** | 18.9"W x 9.25"H x 9.84"D

S-110-1207

UPC Code	Part#	Model#	Description	Wt./Lbs	Case Qty
027418 08161 2		TH110-DP-P	Retail Pack Electronic Programmable DP 16A 240V/208V	.7	6