


# FEDDERS®

## 2008 Room Air Conditioner Specifications

Performance										Electrical Requirements						Features						Cabinet Size			Window Opening		Weight
Model	Cooling Area	BTUH Cooling	BTUH Heating	E.E.R.	Pints Per Hour	Room Air Delivery (CFM max.)	Voltage	Amps Cooling	Amps Heating	Watts Cooling	Watts Heating	Plug Cap. Amps	Receptacle	Air Exchanger	Air Direction	Fan Speed	Auto Restart	Window Mount Type	Slide-Out Chassis	Washable Filter	Additional Features	Width	Depth*	Height	Width (Min/Max)	Height (Min)	Net/Ship Weight(lbs)
<b>WINDOW AIR CONDITIONERS</b>																											
A6K32E7C	1600	32,000	-	8.5	10.0	700	230	18.2	-	3760	-	250/30	D	Yes	4 Way	2	Yes	Rigid	Yes	Yes	-	27	33 1/2	20 5/8	27 1/4 / 40	21	220/234
A7R24E7A	1400	24,000	-	9.4	5.7	460	230	11.6	-	2550	-	250/20	C	Yes	4 Way	3	Yes	Rigid	Yes	Yes	★	26 3/8	26 3/4	17 1/2	26 7/8 / 40	18 5/8	163/178
A6R18E7A	1000	18,000	-	9.7	5.1	460	230	8.2	-	1850	-	250/15	B	Yes	4 Way	3	Yes	Rigid	Yes	Yes	-	26 3/8	26 3/4	17 1/2	26 7/8 / 40	18 5/8	132/152
A7R15E2A	800	14,500	-	10.8	4.2	450	115	11.5	-	1340	-	125/15	A	Yes	4 Way	3	Yes	Rigid	Yes	Yes	★	26 3/8	26 3/4	17 1/2	26 7/8 / 40	18 5/8	128/150
A6R12F7A	550	12,000	-	9.8	3.2	295	230	5.4	-	1220	-	250/15	B	Yes	4 Way	3	Yes	Flex	-	Yes	-	19 5/8	19 5/8	13 3/4	20 / 39	14 1/4	73/81
A6R12F2A	550	12,000	-	9.8	3.2	295	115	11.0	-	1220	-	125/15	A	Yes	4 Way	3	Yes	Flex	-	Yes	-	19 5/8	19 5/8	13 3/4	20 / 39	14 1/4	73/81
A6R10F2A	450	10,000	-	9.8	2.3	235	115	9.5	-	1020	-	125/15	A	Yes	4 Way	3	Yes	Flex	-	Yes	-	19 5/8	19 5/8	13 3/4	20 / 39	14 1/4	71/78
A6R08F2A	340	8,000	-	9.8	1.7	205	115	7.2	-	820	-	125/15	A	-	4 Way	3	Yes	Flex	-	Yes	-	17 3/4	15 3/4	12 3/8	18 / 36	12 7/8	51/55
A6R06F2A	200	6,000	-	9.7	1.3	140	115	5.4	-	620	-	125/15	A	-	4 Way	3	Yes	Flex	-	Yes	-	17 3/4	15 3/4	12 3/8	18 / 36	12 7/8	46/51
A6R05F2A	150	5,000	-	9.7	1.3	130	115	5.2	-	515	-	125/15	A	-	2 Way	3	Yes	Flex	-	Yes	-	17 3/4	13	11 3/8	18 / 36	11 7/8	38/43
A3R05F2A	150	5,000	-	9.7	1.3	130	115	5.2	-	515	-	125/15	A	-	2 Way	2	No	Flex	-	Yes	M	17 3/4	13	11 3/8	18 / 36	11 7/8	38/43
<b>HEAT / COOL AIR CONDITIONERS</b>																											
AER24E7A	1400	23,800	16,000	8.5	5.7	480	230	11.6	21.0	2640	4900	250/30	D	Yes	4 Way	3	Yes	Rigid	Yes	Yes	H/C	26 3/8	26 3/4	17 1/2	26 7/8 / 40	18 5/8	163/178
AER18E7A	1000	18,000	16,000	9.7	5.1	480	230	8.2	21.0	1850	4900	250/30	D	Yes	4 Way	3	Yes	Rigid	Yes	Yes	H/C	26 3/8	26 3/4	17 1/2	26 7/8 / 40	16 1/4	139/158
AER12E7A	550	12,000	10,000	9.8	3.2	270	230	5.4	13.4	1220	3080	250/20	C	Yes	4 Way	3	Yes	Rigid	Yes	Yes	H/C	23 7/8	24	15 3/4	19 / 40	14 1/4	95/110
AER08F2A	340	7,800	4,000	9.8	1.7	190	115	7.0	10.3	800	1260	125/15	A	Yes	4 Way	3	Yes	Flex	-	Yes	H/C	18 1/2	18 1/8	13 3/4	19 / 40	14 1/4	86/105
<b>THROUGH-THE-WALL AIR CONDITIONERS</b>																											
AET12W7A	550	12,000	10,000	9.4	3.0	255	230	5.9	13.7	1270	3120	250/20	C	Yes	4 Way	3	Yes	Wall	Yes	Yes	★H/C	24	22	14 1/2	N/A	N/A	83.5/97
A7T12W7A	550	12,000	-	9.4	3.0	265	230	5.9	-	1270	-	250/15	B	Yes	4 Way	3	Yes	Wall	Yes	Yes	★	24	22	14 1/2	N/A	N/A	83.5/97
A7T10W7A	450	10,000	-	9.4	2.3	265	230	4.8	-	1060	-	250/15	B	Yes	4 Way	3	Yes	Wall	Yes	Yes	★	24	22	14 1/2	N/A	N/A	81.5/95
A7T10W2A	450	10,000	-	9.4	2.3	265	115	9.5	-	1060	-	125/15	A	Yes	4 Way	3	Yes	Wall	Yes	Yes	★	24	22	14 1/2	N/A	N/A	81.5/95
A7T08W2A	340	8,000	-	9.4	1.9	275	115	7.6	-	850	-	125/15	A	Yes	4 Way	3	Yes	Wall	Yes	Yes	★	24	22	14 1/2	N/A	N/A	79/88
<b>SLIDER / CASEMENT AIR CONDITIONERS</b>																											
A6R12S2A	550	12,000	-	9.3	3.2	285	115	11.2	-	1260	-	125/15	A	Yes	4 Way	3	Yes	Slider	-	Yes	-	14 1/2	24 3/4	20 1/2	15 1/2	21	88/99
A6R10S2A	450	10,000	-	9.3	2.6	285	115	9.3	-	1050	-	125/15	A	Yes	4 Way	3	Yes	Slider	-	Yes	-	14 1/2	24 3/4	20 1/2	15 1/2	21	84/92
<b>PORTABLE AIR CONDITIONERS</b>																											
AEPO9D2C	400	9000	4500	7.5	3.8	400	115	7.5	12.0	800	1380	125/15	A	-	2 Way	3	Yes	Port.	-	Yes	H/C	17	17	33	N/A	N/A	80/85
A6PO9S2C	400	9000	-	7.5	1.75	170	115	7.5	-	800	-	125/15	A	-	2 Way	3	Yes	Port.	-	Yes	-	13 3/4	20 5/8	35 1/4	N/A	N/A	80/85

### Receptacle Key



Models designated 230 Volts are designed to operate at a minimum of 197 Volts.

All models have electronic controls unless otherwise noted.

H/C - Models with electric heat. M - Mechanical controls.

★ - ENERGY STAR® qualified model. \* Cabinet Depth includes decorative front.

**MODELS AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.**

All product specifications reflect available information at the printing of this specification sheet. Fedders reserves the right to revise or modify products and/or specifications without notice.

©2008 Fedders North America, Inc. Fedders is a registered trademark of Fedders North America, Inc.

**FEDDERS®**

Fedders Corporation 505 Martinsville Rd. Liberty Corner, NJ 07938 USA

[www.fedders.com](http://www.fedders.com)