

Ceiling Grid Covers

GridMAX®

ACP
Sound Ideas. Proven Products.

Change the look, not the ceiling

3 fast, simple steps

Easy-to-Follow Instructions On Back

Saves cost and time of reinstallation

See your sales associate or the back of this sheet to Special Order

Install the wall molding cover

1



Install the 4' main cover

2



Install the 2' tee cover

3



Compare GridMAX to painting or reinstallation

	GridMAX	Painting	Reinstallation
Wide range of colors & finishes	●	●	
Doesn't rust or show scratches	●		
Saves time	●		
Cost effective	●		
Easy for one person to install	●		
High grade PVC plastic easy to cut and use	●		
4' sections are easy to get home	●		
OSHA certified option	●	●	●
Easy to determine how many of each components to buy	●		

Questions?

1.800.558.0615 • acpideas.com

For successful results, read and follow the detailed instructions on back

Ceiling Grid Covers

Finish # and Name

- 00 Paintable White
- 04 Brass
- 05 Chrome
- 08 Brushed Aluminum
- 17 Bermuda Bronze
- 19 Cracked Copper
- 20 Muted Gold
- 18 Moonstone Copper
- 09 Argent Silver
- 24 Argent Gold
- 10 Argent Copper
- 11 Copper Fantasy
- 21 Crosshatch Silver
- 25 Polished Copper
- 26 Oil-Rubbed Bronze
- 27 Smoked Pewter
- 12 Light Maple
- 13 Pearwood
- 14 Welsh Cherry
- 16 Verdigris



Easy-to-Follow Instructions


Tools you will need



What comes in a GridMAX kit?


This kit is for a 100 sq ft room.

- (12) 4' wall molding covers
- (14) 4' main covers
- (28) 2' tee covers (You will have extra 2' tees once installed correctly.)



2' x 4' Ceiling Panel & Grid System

Existing Metal Grid
GridMAX Wall Molding Caps
GridMAX 4' Main
GridMAX 2' Tee



Step 1 INSTALL WALL MOLDING COVERS

Install the wall molding covers by sliding the cover over the existing metal wall angles. Continue to install the covers by abutting them end-to-end around the entire room. (See Tip #1)


Step 2 INSTALL 4' MAIN COVERS

Install the 4' main covers over the existing metal grid by placing them parallel to each other every 48" on-center. The 4' main covers should be installed along the 4' side of the tile.

Measure and cut your first 4' main cover so the notch is aligned over the first metal grid intersection. (See Tip #2) Install the 4' main cover by sliding the longer flange over the lip of the existing metal grid. Then simply slide your thumb down the middle or the opposite edge and snap the cover on. The remaining 4' main covers in that row will line up by simply abutting the end of the next 4' main cover to the end of the already installed 4' main cover. When each row is complete, cut the last 4' main cover so it ends at the wall bracket cover.

2' x 2' Ceiling Panel & Grid System

Existing Metal Grid
GridMAX Wall Molding Caps
GridMAX 4' Main
GridMAX 2' Tee



Step 1 INSTALL WALL MOLDING COVERS

Install the wall molding covers by sliding the cover over the existing metal wall angles. Continue to install the covers by abutting them end-to-end around the entire room. (See Tip #1)

Step 2 INSTALL 4' MAIN COVERS

Install the 4' main covers over the existing metal grid by placing them parallel to each other every 24" on-center. The 4' main covers can be installed parallel in either direction. It is suggested that you place the 4' main covers over the existing metal mains.

Measure and cut your first 4' main cover so the notch is aligned over the first metal grid intersection. (See Tip #2) Install the 4' main cover by sliding the longer flange over the lip of the existing metal grid. Then simply slide your thumb down the middle or the opposite edge and snap the cover on. The remaining 4' main covers in that row will line up by simply abutting the end of the next 4' main cover to the end of the already installed 4' main cover. When each row is complete, cut the last 4' main cover so it ends at the wall bracket cover.

Step 3 INSTALL THE 2' TEE COVERS

The 2' tee covers are installed perpendicular to the 4' main covers.

Step 3 INSTALL THE 2' TEE COVERS

The 2' tee covers are installed perpendicular to the 4' main covers.

INSTALLATION TIPS

TIP 1: At each room corner, measure the distance from the last cover to the inside corner and cut the wall molding cover at a 45° angle using a tin snips or a pair of scissors.

TIP 2: Starting at the wall, measure the length from the wall molding cover to the first intersection. Using the length, measure from the start of the notch towards the end and cut off the excess. (If the measurement is greater than 12" measure and cut from the second notch.)

TIP 3: When installing on a 2' x 4' grid system, every-other notch on the mains will fall onto the metal grid intersections.

For additional tips and information visit: acpideas.com

Tech Support
1-800-558-0615
acpideas.com

Ceiling Grid Covers
GridMAX

ACP
Sound Ideas. Proven Products.
(REV: 09.08) G12-99 - Kit & Generic
GridMAX patent numbers: 6,305,137; 6,536,173; 6,324,806