

AP120-SL SERIES

Ventilation Fan with 10W 3000K LED Light



Description:

Slim Fit ventilating fan shall be ultra-quiet, ceiling or wall mount engineered for continuous operation. Suitable for new construction or remodeling. Light Source is 3000K 1100 Lumens LED Light. Suitable for new construction or remodeling. ENERGY STAR qualified and HVI certified. ETL/cETL listed for use in insulated ceilings.(Type I.C.).

Motor/Blower:

- Permanently lubricated high performance AC motor.
- Engineered for continuous operation.
- Power rating shall be 120v/60Hz.
- Fan shall be UL and cUL listed for tub/shower enclosure when GFCI protected.
- Motor equipped with thermal shut-off.

Housing:

- 26 GA Galvanized Steel Body
- Detachable 4" & 6" Duct connector
- Built-in damper
- 2—24" expandable anti-vibration brackets included.
- Designed for installation in ceilings with a minimum of 6" clearance.

Grille:

Contemporary design, wipes clean. Attaches to housing with torsion springs. Round on square design.

Finishes: White (W).

Light: Non-dimmable 10W, 3000K, 1100 Lumens LED Light Panel.

Ventilating Area:



For bathrooms up to 120 square feet.

Warranty:

6 Years when installed by licensed professional.

Architectural Specifications:

Ventilation fan will be ceiling or wall mount, ENERGY STAR qualified, with no less than 120CFM and no more than 0.7 Sones as certified by HVI at 0.1 static pressure in inches water gauge. Power consumption shall be no greater than 33 watts and ENERGY STAR rated with an efficiency rating of no less than 3.8 CFM/watt. The motor will be permanently lubricated, engineered for continuous operation. Light source shall be a 10W 3000K LED Light panel. Duct diameter will be 4" or 6" round. Fan shall be listed for tub/shower enclosure when used with GFCI branch circuit wiring and shall be ETL/cETL listed for use in insulated ceilings (Type I.C.). Fan shall be ASHRAE 62.2, LEED, California Title 24 and Washington VIAQ compliant.



W

| Model: AP120 Series | 4" Duct | |
|-------------------------------|-------------------|------|
| Static Pressure (inches w.g.) | 0.1 | 0.25 |
| Air Volume (CFM) | 120 | 111 |
| Noise (Sones) | 0.7 | n/a |
| Power Consumption (Watts) | 33 | 32.3 |
| Energy Efficiency (CFM/Watts) | 3.8 | 3.4 |
| Current (Amps) | 0.28 | 0.27 |
| ENERGY STAR rated | YES | |
| Grille Dimensions | 13 3/8" x 13 3/8" | |



| Model | Qty | Comments | Project |
|-------|-----|----------|---------------|
| | | | Location |
| | | | Architect |
| | | | Engineer |
| | | | Contractor |
| | | | Submitted by: |
| | | | Date: |