



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Apex LED Pendant APP Series

### Features

This modern double layer drum design provides a dramatic look and features LumaFuse™ laminated fabric/acrylic shade in 2 colors. White bottom acrylic diffuser disperses the light. Suspended with a 3 ft. adjustable rigid stem expandable up to 9 ft.

### Construction

Metal housing and canopy. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

### Finish

Solid wood accent.  
Satin Nickel canopy and stems.

### Diffuser

LumaFuse™ laminated fabric/acrylic front shade in Jute or Linen White.  
White bottom acrylic diffuser

### Electrical

Input 120-277 VAC 60 HZ.  
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.  
TRIAC and ELV dimming only at 120 VAC.

### LED

Integrated LED modules capable of producing:  
14" - 18W = 1400 source lumens  
17" - 30W = 2400 source lumens  
21" - 42W = 3200 source lumens  
Adjustable Choice 3000K, 3500K, 4000K (CCT).  
Rated for 50,000 Hrs, 90 CRI.

### Certification

All fixtures are cETLus listed for indoor damp locations.  
\*Title 24/JA8 Compliant

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date-of-purchase.

Specifications and dimensions  
subject to change without notice.

## Ordering Information:

Espresso/Jute	Weathered Grey/Jute	LED	Source Lumens	Adjustable CCT	DIA.	H
APP1214LAJUDES-JT	APP1214LAJUDWG-JT	18W	1400	3000K/3500K/4000K	14-1/4"	4-1/4"
APP1524LAJUDES-JT	APP1524LAJUDWG-JT	30W	2400	3000K/3500K/4000K	17"	4-1/4"
APP1932LAJUDES-JT	APP1932LAJUDWG-JT	42W	3200	3000K/3500K/4000K	21-1/4"	4-1/4"

  

Espresso/Linen White	Weathered Grey/Linen White	LED	Source Lumens	Adjustable CCT	DIA.	H
APP1214LAJUDES-LW	APP1214LAJUDWG-LW	18W	1400	3000K/3500K/4000K	14-1/4"	4-1/4"
APP1524LAJUDES-LW*	APP1524LAJUDWG-LW*	30W	2400	3000K/3500K/4000K	17"	4-1/4"
APP1932LAJUDES-LW*	APP1932LAJUDWG-LW*	42W	3200	3000K/3500K/4000K	21-1/4"	4-1/4"

