



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## Pratt LED Outdoor Ceiling PRTW Series

### Features

Pivoting heads to adjust light direction.  
Ideal use for general lighting in indoor or outdoor residential, commercial, and hospitality applications. Fixture can be mounted to a standard junction box (not included) on a wall or ceiling.

### Construction

Cast metal housing. Back pan is made from 12 gauge stamped aluminum material with matching powder coat finish. Power supply connections must be made inside a junction box (not included).

### Finish

Black, Textured Grey or Oil-Rubbed Bronze\* finish.

### Diffuser

Glass diffuser.

### Electrical

Input 120 VAC / 60Hz.  
Minimum starting temp -4° F/-20° C  
Integrated photocell for dusk to dawn operation.

### LED

Integrated LED modules capable of producing:  
22W = 1900 delivered lumens  
Adjustable Choice 3000K, 4000K, 5000K (CCT).  
Rated for 50,000 Hrs. 80 CRI.


### Certification

All fixtures are cETLus listed for outdoor wet locations.  
Title 24/JA8 Compliant

### Warranty

5 Year Limited Warranty:  
**Restrictions apply based on location.**

**Specifications and dimensions  
subject to change without notice.**



## Ordering Information:

Black	Textured Grey	Oil-Rubbed Bronze	Delivered			H	W	D
PRTW0905LAJENBK	PRTW0905LAJENTG	PRTW0905LAJENZ*	LED	Lumens	Adjustable CCT	5"	9"	7-1/2"
			22W	1900	3000K/4000K/5000K			

\*Minimum order quantity required, consult factory.