

Ryan LED Outdoor Sconce RYNW Series

Features

This outdoor LED light is ideal for security and general lighting. Vertical or horizontal mounting. Fixture mounts to standard junction box (not included).

Construction

Durable metal construction with powder coat finish. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black finish.

Diffuser

White acrylic diffusers.

Electrical

Input 120-277 VAC 60 HZ. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC. Minimum starting temp -4° F / -20°C

Lamping

Fixture includes a LED modules capable of producing: 20W = 400 delivered lumens 25W = 500 delivered lumens 30W = 600 deliveredlumens 40W = 800 delivered lumens Adjustable Choice 2700K, 3000K, 3500K, 4000K, 5000K (CCT).

Certification

All fixtures are cETLus listed for wet locations. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Rated for 50,000 Hrs., 90 CRI.

Ordering Information:

		Delivered				
Black	LED	Lumens	Adjustable CCT	H	W	D
RYNW0618LAJUDBK	20W	400	2700K/3000K/3500K/4000K/5000K	18"	6"	3-1/4"
RYNW0624LAJUDBK	25W	500	2700K/3000K/3500K/4000K/5000K	24"	6"	3-1/4"
RYNW0636LAJUDBK	30W	600		36"	6"	3-1/4"
DVNIMACAOLA ILIDDIZ	4014/	000	27001/70001/75001/40001/50001/	10"	C"	7 1///













