



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Shaw LED Wrap Light (Adjustable CCT) SHAL Series

Features

Modern LED wrap can be used in various applications including corridors, kitchens and public spaces. Fixture mounts to a standard junction box (not included).



Emergency Back-Up (Optional 'BB')

- 90 minute run-time
- 7.4V 2500 mAh Lithium Ion Battery
- 8 watts

Construction

Housing is die-formed of 22-gauge steel. Mounting holes are included. Power supply connections are made inside the junction box (not included). Plastic molded endcaps.



Finish

Housing is finished in lighting grade white baked gloss enamel paint.



Diffuser

Frosted white acrylic diffuser.

Electrical

Input 120-277 VAC/60 HZ
Not compatible with dimmers.

LED

Integrated LED modules capable of producing:
25W = 2000 delivered lumens
40W = 4000 delivered lumens
3000K/4000K/5000K Adjustable CCT
Rated for 50,000 Hrs., 80 CRI.


Certification:

cETLus listed for indoor damp locations.

Limited Warranty:

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.



Ordering Information:

White	LED	Delivered Lumens	Adjustable CCT	L	W	D
SHAL0524LAJMVWH	25W	2000	3000K/4000K/5000K	24"	5-1/4"	2-3/8"
SHAL0548LAJMVWH	40W	4000	3000K/4000K/5000K	47-1/4"	5-1/4"	2-3/8"
SHAL054840LAJMVWH-BB	40W	4000	3000K/4000K/5000K	47-1/4"	5-1/4"	2-3/8"