

24" Built-In Tall Tub Dishwasher

AFITTDW

Performance Features

 Multi-Level Washing for Wash-It-Once Results Variable pressure washing with three spray arms, sensor monitors to assess the soil level of dishes, and a triple filtration system to remove even the smallest particles all work in harmony to make sure your dishes are clean the first time.

Condensate Quick Drv

Moisture condensates on the cooler stainless steel tank and door and drains to the sump area for quick and efficient drying.

Quiet Operation

Three layers of insulation create one of the guietest dishwashers on the market.

• 6 Cycles with 4 Options

Cycles include Pots/Pans Plus (extra-heavy): Pots/Pans (heavy); Regular Wash (normal); Daily Wash (medium); Quick Wash (35 minutes!); Rinse/Hold (pre-rinse).

Options include Half Load to save energy; Auto Tablet detects rinse aid and automatically sets drying time duration; Delay Start lets you delay activation for up to 24 hours; Sanitize brings the water temperature up to NSF requirements.

- » LCD screen displays remaining run time.
- » Floor indicator light discreetly displays on floor while dishwasher is running.

Interior Features

Adjustable Top Rack

Two positions allows you to accommodate taller glasses in the upper rack or larger pans in the bottom rack.

Adjustable Tines on Lower Rack

Four rows of tines can be adjusted for easier loading of pans.

• Stemware Cradles

Two stemware cradles gently hold wine glasses to prevent damage.

• Sliding One-Piece Cutlery Basket

Every load is different. And the sliding cutlery basket makes it easier to fit everything in every load.

· Holds 14 Place Settings













Color Options



Gloss Black AELTTDW-BLK



AELTTDW-MBL



White **AELTTDW-WHT**



Scarlet AELTTDW-SCR



Ivorv AELTTDW-IVY



Stainless Steel AFITTDW-SS





24" Built-In Tall Tub Dishwasher

AELTTDW

Technical Details	
Height (Adjustable)	33-7/8" – 35-7/8"
Width	23-9/16"
Depth	22-3/16"
Depth with 90° Door Open	47-1/4"
Shipping Weight (Approx.)	97 lbs.
Power Supply Location	Back Bottom Middle
Water Inlet Location	Front Bottom Left
Water Usage (Gallons) – Normal Cycle	3.5-5.0
Water Pressure (PSI)	4.35 - 145 psi
Water Heating Element Rating	1240 watts
Inlet Water Temperature	120°F (49°C) required
Electrical Requirement	12 amps, 120V / 60 Hz Includes 4' electrical cord
Number of Wash Levels	6
Sound Level	48dB



