

SPECIFICATIONS SEGOVIA WALL MOUNT RANGE HOODS

600 CFM/14.0 Sones @ 0.10" SP.

• **Dimensions**

Overall bottom projection - $19^{3\!/}\!\!4^{\prime\prime}$ Available widths: $35^{7\!/}\!\!8^{\prime\prime}$

• Hood Body Brushed 430 stainless steel

• Motor

3 speed, permanently split capacitor motor. Rated 120 volts, 60 hz.

• Lighting

Two - GU10 base, MR16, 50 watt halogen lights.

• Ducting Options

Vertical ducting: 6" round duct adapter complete with back draft damper ensuring quiet operation. Ductless: Requiers charcoal filter (not included).

Blower Wheel

Dual inlet, electronically balanced polymetric centrifugal blower wheel, $5^{3_4^{\prime\prime}}$ width 59 paddles.

• Mounting

Wall mounted with included mounting bracket. Install 24" to 30" from cooking surface.

• Filters

Grease Filter: BCGF-01 (included). Charcoal Filter: BCCF-01 (not included).


<u>Available Finishes</u>

Stainless Steel.

		EXPANDED PERFORMAN(Static Pressure (inches of w.g.)						Sones	Fan Speed	Power	
		0	0.1	0.25	0.5	0.75	1.0	@ .1 SP	RPM	Watts	Amps
Air Flow - CFM		603	600	594	578	557	531	14.0	2560	551.0	3.8
PROJECT						ARCHITEO	т				
OCATION						ENGINEER					
CONTRACTOR						SUBMITTED BY		DATE			
FAN MODEL Umber Number	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY		OPTIONAL EQU & Remar		
								Air King: 820 Lincoln Avenue West Chester, Pennsylvania 19380-44 Tel: (610) 692-7400 • 877-304-3785 Fax: (610) 696-8048			

Specifications subject to change without notice.





357/8"