

# Air King

## Ventilation Products®


SPECIFICATIONS

# AS60

CEILING/WALL EXHAUST FAN

**60 CFM/3.5 SONES @ 0.10" WG. – HVI CERTIFIED**  
**120 Volts, 0.90 amps, 60 hz.**

- **GRILL**  
White, polymeric grill held firmly in place with torsion springs; easily removed if necessary, dimensions - 10"x10".
- **BLOWER WHEEL**  
One piece polymeric wheel, 4 1/2" diameter, 1.0" wide, with 10 fins.
- **MOTOR**  
Single coil plug-in, two pole motor, life time lubrication, thermally protected. Rated 120 volts, 60 hz., 0.90 amps.
- **HOUSING**  
23 ga. galvanized metal housing, 7 3/8" x 7 1/2" x 3 3/4" double metal thickness mounting tabs.
- **DUCT COLLAR**  
Plastic collar for 3" duct connection, comes complete with built in non-metal damper for quiet operation.
- **VENTILATED AREA**  
For bathrooms up to 60 sq. ft. for other rooms up to 75 sq. ft.



**CUL/UL/HVI**

Certified for use over tub or shower when installed in a GFCI protected branch circuit.

- **UNIT MOUNTING**  
Rated for ceilings insulated to R-40. Designed for ceiling or wall mounting on joists sized down to 2"x4". Unit housing will mount through drywall thickness up to 3/4". Rough-in opening 7 3/4" x 7 3/4".
- **SINGLE PACK SHIPPING INFO**
  - Box Dim 10 3/4" x 10 1/8" x 4 3/4"
  - UPC 0-8316226311-7
  - Shipping Weight - 4 1/2 lbs.

HVI PERFORMANCE									
Static pressure (inches of w.g.)	0	0.05	0.1	0.15	0.2	0.25	0.3	0.35	0.4
CFM	67	65	61	55	50	44	30	13	10
RPM	2209	2359	2598	2655	2690	2732	2722	2708	2692
WATTS	69	65	63	62	62	62	62	62	62

Air-King bathroom fans are tested by the Air Movement and Control Association (AMCA) in accordance with HVI test standard 916, (Air Flow Test Standard) and HVI test standard 915 (Procedure For Loudness Rating Of Residential Fan Products). The Performance results are certified and verified by the Home Ventilating Institute (HVI).

<b>PROJECT</b>							<b>ARCHITECT</b>			
<b>LOCATION</b>							<b>ENGINEER</b>			
<b>CONTRACTOR</b>							<b>SUBMITTED BY</b>			<b>DATE</b>
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



THIS PRODUCT IS TESTED & CERTIFIED BY UNDERWRITERS LABORATORIES INC. TO UL STANDARD UL-507 ELECTRIC FANS & CSA STANDARD C22.2 No. 113 FANS & VENTILATORS. UL FILE #E20739.



U.S.: 820 Lincoln Avenue  
 West Chester, Pennsylvania 19380-4466  
 Tel: (610) 692-7400 • 1-877-304-3785  
 Fax: (610) 696-4648

Canada: 110 Glidden Road  
 Brampton, Ontario L6T 2J3  
 Tel: (905) 456-2033  
 Fax: (905) 456-1015