





300 CFM/5.5 Sones @ 0.10" SP. Horizontal 300 CFM/5.5 Sones @ 0.10" SP. Vertical

Dimensions

Overall bottom projection - 22" Height -71/2" Widths - 30", 36"

Hood Body

Stainless Steel: 24 gauge, grade 430 stainless steel.

Motor

Variable speed, thermally protected, permanently lubricated motor. Rated 120 volts, 60 hz. with two electronically balanced blower wheels.

Lighting

Two - GU10 base, MR16, 50 watt halogen lights (bulbs not included).

Ducting Options

Horizontal ducting: 3¼"x10" (duct adapter and damper included). Vertical ducting: 3¼"x10" (duct adapter and damper included). Ductless: top vent (charcoal filter not included).

Mounting


Wall mounted. Install 20" to 30" from cooking surface.


Filters

Grease Filter: GF-01 (included). Charcoal Filter: CF-01 (not included).

Available Finishes

Stainless Steel





EXPANDED PERFORMANCE											
		Stati	c Pressure	e (inches d	Sones	Fan Speed	Power				
Air Flow - CFM	0	0.05	0.1	0.15	0.2	0.25	@ .1 SP	RPM	Watts	Apms	
Vertical Ducting High	337	324	300	294	277	258	5.5	1575	114.0	1.5	
Horizontal Ducting High	330	317	300	280	259	239	5.5	1560	114.0	1.5	

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITT	SUBMITTED BY DATE		
FAN NUMBER	MODEL NUMBER	СҒМ	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	





U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785

Fax: (610) 696-8048

Canada: 8 Edvac Drive Brampton, Ontario L6S 5P2 Tel: (905) 456-2033 • 800-250-8767 Fax: (905) 456-1015

Specifications subject to change without notice.