ABT-FRP-14-TS
ABT-FRP-14-TS TempLog Premier Flammable Storage Refrigerator 14 Cu. Ft. capacity One solid swing door, right hinged, not reversible Microprocessor temperature controller Adjustable operating temperature range: 1°C - 10°C Touch Screen Digital Temperature Display and Alarm Module Password-protected control panel Sample simulated digital temperature display; .1° Resolution, adjustable temperature display in Celsius or Fahrenheit Active temperature scale bar display Resettable 1-point min/max history Digital 24-hour temperature chart Temperature data logging USB port for data transfer and software updates Real-time operational display clock 4-20mA output Electronic troubleshooting guide Electronic troubleshooting guide Electronic troubleshooting guide Electronic alarm volume Audible and visual high/low temperature alarms Sensor error alarm Power failure alarm Door ajar alarm Low battery alarm Operation indicator Alarm validation (audible, visual, and remote alarm) Alarm mute with ring back Remote alarm contacts One adjustable/two fixed shelves Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Leveling legs One probe access port (3/8") White textured cabinet and door High density urethane foam cabinet and door insulation CFC-free refrigerant (R134a), foam insulation and packaging Three year parts and labor warranty Quality certified with 100% unit temperature testing Exterior dimensions: 29 ¾ "W x 36 5/8 "D x 61 ½ "H Cycle defrost 115V, 60 Hz, 5 Amps, 1/3 HP UL/C-UL listed
Units meet NFPA guidelines 45 and 70 Shipping weight: 236 lbs.