Description: Premier Pharmacy/Vaccine Refrigerator & Freezer Combination 9 Cu. Ft. Capacity (4.6 Ref./4.2 Freezer) Two stainless steel exterior swing doors, left hinged, not reversible Microprocessor temperature controller, refrigerator and freezer Digital temperature display, refrigerator and freezer Adjustable operating temperature range: Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C25°C) Two Refrigerator/Freezer freestanding thermometers with 3 year certificate of calibration, with min/max memory, °F/°C switchable Audible and visual high and low temperature alarms, refrigerator and freezer Remote alarm contacts, refrigerator and freezer 2 adjustable/1 fixed shelves refrigerator/2 fixed shelves freezer with guard rails on back in Refrigerator to prevent product from being pushed against back wall Back wall evaporator cover, Refrigerator Forced draft circulation Refrigerator Cord label stating Warning! Do not unplug the appliance or break circuit. Expensive vaccine in storage Keyed door locks Magnetic door gasket for positive seal Recessed door handles Leveling legs Stacking kit LED interior lights Probe access port (3/8"), 2 ea. (1 for refrigerator/1 for freezer) Stainless steel exterior HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Quality certified with 100% unit temperature testing Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 23 %" W x 24 ½"D x 66 ¾"H Manual defrost freezer / cycle defrost refrigerator 115V, 60 Hz, 1.74 Amps Refrigerator, 1.5 Amps Freezer, 1/8 HP Refrigerator and Freezer UL/C-UL listed Shipping weight: 230 lbs. *Please note this unit requires 2 outlets.	Product Name:	PH-ABT-HC-RFC9SS-LH
Cu. Ft. Capacity (4.6 Ref./4.2 Freezer) Two stainless steel exterior swing doors, left hinged, not reversible Microprocessor temperature controller, refrigerator and freezer Digital temperature display, refrigerator and freezer Adjustable operating temperature range: Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C25°C) Two Refrigerator/Freezer freestanding thermometers with 3 year certificate of calibration, with min/max memory, °F,°C switchable Audible and visual high and low temperature alarms, refrigerator and freezer Remote alarm contacts, refrigerator and freezer 2 adjustable/1 fixed shelves refrigerator/2 fixed shelves freezer with guard rails on back in Refrigerator to prevent product from being pushed against back wall Back wall evaporator cover, Refrigerator Cord label stating Warning! Do not unplug the appliance or break circuit. Expensive vaccine in storage Keyed door locks Magnetic door gasket for positive seal Recessed door handles Leveling legs Stacking kit LED interior lights Probe access port (3/8"), 2 ea. (1 for refrigerator/1 for freezer) Stainless steel exterior HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Quality certified with 100% unit temperature testing Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 23 %" W x 24 ½"D x 66 %"H Manual defrost freezer / cycle defrost refrigerator 115V, 60 Hz, 1.74 Amps Refrigerator, 1.5 Amps Freezer, 1/8 HP Refrigerator and Freezer UL/C-UL listed Shipping weight: 230 lbs.		
		Premier Pharmacy/Vaccine Refrigerator & Freezer Combination 9 Cu. Ft. Capacity (4.6 Ref./4.2 Freezer) Two stainless steel exterior swing doors, left hinged, not reversible Microprocessor temperature controller, refrigerator and freezer Digital temperature display, refrigerator and freezer Adjustable operating temperature range: Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C25°C) Two Refrigerator/Freezer freestanding thermometers with 3 year certificate of calibration, with min/max memory, °F/°C switchable Audible and visual high and low temperature alarms, refrigerator and freezer Remote alarm contacts, refrigerator and freezer 2 adjustable/1 fixed shelves refrigerator/2 fixed shelves freezer with guard rails on back in Refrigerator to prevent product from being pushed against back wall Back wall evaporator cover, Refrigerator Forced draft circulation Refrigerator Cord label stating Warning! Do not unplug the appliance or break circuit. Expensive vaccine in storage Keyed door locks Magnetic door gasket for positive seal Recessed door handles Leveling legs Stacking kit LED interior lights Probe access port (3/8"), 2 ea. (1 for refrigerator/1 for freezer) Stainless steel exterior HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Quality certified with 100% unit temperature testing Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 23 %/" W x 24 ½"D x 66 %/"H Manual defrost freezer / cycle defrost refrigerator 115V, 60 Hz, 1.74 Amps Refrigerator, 1.5 Amps Freezer, 1/8 HP Refrigerator and Freezer UL/C-UL listed
1 10000 11010 tillo dillictoquillo 2 oddoto.		Please note this unit requires 2 outlets.