

Features

- 3000K color temperature with 90+ CRI
- 4" and 6" trim sizes with up to 1050 lumens
- Low profile design, as little as 1" high
- Quick and easy design for fast installs
- Polycarbonate lens for diffused soft light
- Dimmable with most ELV and TRIAC dimmers
- 35,000 hours rated life
- ENERGY STAR and JA8 Certified
- cETLus Listed for wet locations
- Suitable for use in closets based on NFPA 70, NEC section 410.16 (A)(3) and 410.16 (C)(5)) (QD4PIR and QD6PIR Only)

Available Finishes



White

Dimming Options

- TRIAC (10-100%)
- CL (10-100%)
- ELV (10-100%)

(PIR is non-dimmable)

Listing / Ratings













Quick Disc Series

The Quick Disc is a surface mount LED downlight for use with most standard junction boxes. Installation is fast and easy due to its unique screw-through mounting system that connects the downlight straight to the junction box. The Quick Disc is also available in a non-dimmable motion sensing version in both 4" and 6" sizes.

Technical Information

Series	QD
Input Voltage	120V AC, 60Hz
CCT	3000K / 4000K (QD6 only)
CRI	90+
Wattage	9W / 15W
Lumens	650Lm / 1050Lm
Beam Angle	120°
Dimmable	TRIAC / CL / ELV 10-100% / (PIR) non-dimmable
Mounting	Surface mount
Rating	cETLus Listed; Suitable for wet locations
Rated Life	35,000 hrs

Ordering Information

QD4-30-WH	Quick Disc 4" - White / 3000K / 650Lm / 9W / TRIAC
QD4PIR-30-WH	Quick Disc 4" - White / 3000K / 600Lm / 10W / 0-10V
QD6-30-WH	Quick Disc 6" - White / 3000K / 1050Lm / 15W / TRIAC
QD6-40-WH	Quick Disc 6" - White / 4000K / 1050Lm / 15W / TRIAC
QD6PIR-30-WH	Quick Disc 6" - White / 3000K / 950Lm / 15W / 0-10V

Quick Disc Series Downlights



QUICK DISC 4 QD4-30-WH 120V AC / 3000K / 650Lm / 9W





QUICK DISC 6 QD6-30-WH 120V AC / 3000K / 1050Lm / 15W QD6-40-WH 120V AC / 4000K / 1050Lm / 15W





QUICK DISC 6 PIR (Motion Sensor) QD6PIR-30-WH

120V AC / 3000K / 950Lm / 15W