



Features

- Excellent color rendering (90+ CRI)
- Modern surface mount design
- Up to 1200 lumen output performance
- 3000K color temperature with 90+ CRI
- Available in 5" and 7" fixture sizes
- Surface mount installation to most standard 1-1/2" deep octagonal junction boxes
- Battery back-up accessory available
- Dimmable with most TRIAC dimmers
- cETLus Listed for wet locations
- 35,000 hours rated life
- ENERGY STAR certified

Available Finishes



White

Dimming Options

- TRIAC (10-100%)
- 0-10V

Listing / Ratings



NIVO Series Downlight

Ultra slim and modern sleek, the Nivo series downlight features an edgeless surface mount design that blends seamlessly into its surroundings. With uniform light output, the Nivo produces up to 1200 vivid lumens in a 3000K warm white color temperature. Available in two fixture sizes, 5" and 7", as well as a battery back-up option accessory for use in both residential and commercial applications.

Technical Information

Series	NV5 / NV7
Input Voltage	120-277V AC, 60Hz
CCT	3000K
CRI	90+
Wattage	10W / 15W / 20W (Battery Back-up)
Lumens	750Lm / 1200Lm
Beam Angle	120°
Dimmable	TRIAC 10-100% / 0-10V Dimming
Mounting	Surface Mount
Rating	cETLus Listed; Suitable for wet locations
Rated Life	35,000 hrs

Ordering Information

NV5-30-WH	Nivo 5" - White / 3000K / 750Lm / 10W / TRIAC
NV5-0/10V-30-WH	Nivo 5" - White / 3000K / 750Lm / 10W / 0-10V
NV7-30-WH	Nivo 7" - White / 3000K / 1200Lm / 15W / TRIAC
NV7-0/10V-30-WH	Nivo 7" - White / 3000K / 1200Lm / 15W / 0-10V
NV7-BB-WH	Nivo 7" - Battery Back-up Accessory (non-dimmable)

Nivo Series Downlights



NIVO 5 SURFACE MOUNT

NV5-30-WH (120-277V / 3000K / 750Lm / 10W / TRIAC)
NV5-0/10V-WH (120-277V / 3000K / 750Lm / 10W / 0-10V)



NIVO 7 SURFACE MOUNT

NV7-30-WH (120-277V / 3000K / 1200Lm / 15W / TRIAC)
NV7-0/10V-WH (120-277V / 3000K / 1200Lm / 15W / 0-10V)



NIVO 7 BATTERY BACK-UP ACCESSORY

NV7-BB-WH
 120-277V AC / Non-Dimmable
 (Requires NV7 Light Fixture)