



## Features

- Constant voltage non-dimming plug-in driver
- Available in 12V and 24V options
- Wattages ranging from 40W up to 96W
- 6ft 18AWG power cord with 3-prong plug
- 5ft 18AWG tail with male DC jack
- cULus Listed (dry locations)

## Wattage/Voltage Options

- 40W (12V DC | 24V DC)
- 60W (24V DC)
- 90W (24V DC)
- 96W (12V DC)

### 2-wire DC Adapter Accessory (DC-VPI)



### 2-wire DC Adapter Accessory (DC-HW)



## Listing / Ratings



## PS Plug-in Series

Use one of these five constant voltage DC power supplies for non-dimming plug-in applications, based on the capacity and voltage needed. The DC-HW accessory can be used with Trulux tape light, ideally with a switched outlet since the driver does not include an inline switch. Use the DC-VPI for powering low voltage products with bare leads, such as LightStar reels. cULus Listed for use in dry locations.

## Technical Information

Series	PS Plug-in 12V/24V
Max Load	See ordering information
Minimum Load	N/A
Input Voltage	120V AC
Output Voltage	12V DC/24V DC
Dimmable	N/A
Input Wire	6ft 18AWG power cord + 3-prong plug
Output Wire	5ft 18AWG tail with male DC jack
Rating	cULus Listed (dry locations)
Dimensions	5-3/4"L x 2"W x 1-1/4"H (40W) 6-3/4"L x 2-3/8"W x 1-1/4"H (90W/96W)

## Ordering Information

<b>PS-40-12VPI</b>	PS Plug-in 12V DC - 40W Driver
<b>PS-96-12VPI</b>	PS Plug-in 12V DC - 96W Driver
<b>PS-40-24VPI</b>	PS Plug-in 24V DC - 40W Driver
<b>PS-60-24VPI</b>	PS Plug-in 24V DC - 60W Driver
<b>PS-90-24VPI</b>	PS Plug-in 24V DC - 90W Driver
<b>DC-VPI</b>	2-wire DC adapter cable - Bare wire to Female DC
<b>DC-HW</b>	2-wire DC adapter cable - Bare wire to Male DC



## Features

- Class 2 12W Constant voltage dimmable plug-in driver (15-100% control with most TRIAC dimmers)
- Features terminal block for easy wiring and in-line rocker switch on power cord for convenient On/Off control
- 6ft 18AWG power cord with 2-prong plug
- 6ft lead wire with attached terminal block
- cETLus Listed as a Recognized Component (dry locations)

## Wattage/Voltage Options

- 12W (12V DC)

## Listing / Ratings



## PS Plug-in Series - 12W

This low profile dimmable plug-in driver has wire cover strain reliefs at both primary and secondary sides. It includes an attached terminal block to quickly connect low voltage lead wires. For dimming applications, a 4W minimum load must be met.

## Technical Information

Series	PS Plug-in 12V
Max Load	12W
Minimum Load	3W (non-dimming); 4W (dimming)
Input Voltage	100-120V AC, 50/60Hz
Output Voltage	12V DC
Dimmable	15-100% (with TRIAC for most products)
Input Wire	6ft 18AWG power cord + 2-prong polarized plug
Output Wire	5ft 24AWG tail with 4-port terminal block
Rating	cETLus Recognized (dry locations)
Dimensions	5-1/4"L x 2"W x 11/16"H

## Ordering Information

<b>PS-12-12VPI-T</b>	PS Plug-in 12V - 12W Driver
----------------------	-----------------------------