

Features

- Energy efficient LED Flexbrite consumes up to 1 watt per foot
- Dimmable 5-100%*
- Suitable for indoor/outdoor use
- 60,000 hours rated life

Available Colors



3000K

Dimming Options

- ELV (5-100%*)
- LED/CL (5-100%*)

Listing / Ratings⁺



LED Flexbrite Bulk Reels

Two color temperatures of white LED light and five vibrant LED colors are available in 120V 150ft reels. Easy to use flexible, dimmable, and economical LED rope light has UV inhibitor built into the PVC housing for use outdoors. Save 73% in running costs compared to incandescent rope light. LED Flexbrite last up to three times as long as incandescent rope.

Technical Information

Series	LED-MRL			
Input Voltage	120V AC, 60Hz			
CCT	WW			
CRI	72+ (WW)			
Wattage	1W per ft			
Lumens	See individual product			
Max Run	150 feet			
Cuttable	See individual product [†]			
IP Rating	IP65**			
Dimmable	5-100%*			
Rating	indoor/outdoor use			
Rated Life	60,000 hrs			

*Minimum loads may apply. Per the NEC, switched wall outlets cannot be used with wall dimmers.

**IP65 rated only when used with pre-attached molded power cord and end cap is either preattached or properly sealed with dielectric grease, silicone and shrink tube





3/8" LED Flexbrite Bulk Reels 120V / 3%" Diameter / 150ft Reel

FLEXBRITE BULK REELS ORDERING INFORMATION

ITEM NUMBER	ССТ	LENGTH	LUMENS / FT	WATTAGE / FT	IP RATING	CRI	DIAMETER (CUTTING
LED-MRL-WW-150	3000K	150 ft	32Lm / ft	1W / ft	IP65	72+	3/8"	36" [†]

120V Bulk Reels Include: (5) 5ft power connector kits with fused plug (one is pre-attached), (1) pre-attached end cap, and (50) mounting clips †UL Listing for 120V is void if product is cut

FLEXBRITE BULK REELS ACCESSORIES

ITEM NUMBER	DESCRIPTION				
MRL-LED-CONKIT-1.6A	5ft 3/8" diameter power connection kit w/Plug*				
MRL-INVSPL	3/8" diameter invisible splice connector				
MRL-CLIP/SCREW	3/8" diameter clear plastic mounting clips (qty 10)				
MRL-TRACK-4	3/8" diameter clear plastic mounting track (4')				





MRL-LED-CONKIT-1.6A MRL-INVSPL





*Non-UL Listed