

ASSEMBLY INSTRUCTIONS

ITEM NUMBER#89029 |Waldorf Large Chandelier

ITEM DESCRIPTION

MATERIAL TYPE: STEEL.GLASS FINISH :ANTIQUE BRASS.CLEAR TOP COAT/SEALANT:
 SOCKET TYPE: E12 BAKELITE SOCKET QTY:8
 BULB TYPE: TYPE B BULB WATTAGE: 40W VOLTAGE:110V-120V
 ITEM NET WEIGHT:



UL COMPLAINT
 INSTALLATION ENVIRONMENT:SUITABLE FOR DAMP LOCATIONS


NOTE:

*YOUR PRODUCT(S) MAY BE PACKED IN MORE THAN ONE CARTON
 *THIS ITEM MAY REQUIRE PERIODIC TIGHTENING


PARTS

A	MOUNTING PLATE	1 PC
B	CANOPY	1 PC
C	COLLAR LOOP	1 PC
D	RODS	3 PCS
E	SPHERE BOX	1 PC
F	BODY	1 PC
L	LGE ARROW	28 PCS
M	MED ARROW	14 PCS
S	SMALL ARROW	28 PCS
G	RIDGE GLASS	14 PCS

INCLUDED ASSEMBLY HARDWARE



PRODUCT ASSEMBLY



ASSEMBLY INSTRUCTIONS

- 1.REMOVE ALL PACKING CONTENTS FROM THE CARTON(S)CAREFULLY
- 2.REMOVE ALL PARTS FROM THE PACKAGE(S) CAREFULLY
- 3.PLEASE BE SURE YOU HAVE ALL PARTS INDICATED BEFORE YOU BEING ASSEMBLY
- 4.SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER
- 5.SCREW THE METAL "ARROWS" AND RIDGE GLASS ON THE DESIRED THREADING PITCHES ON SPHERE BOX(E) AS PAGE 2 ILLUSTRATIONS.**
6. SCREW THE ROD(D3) TO THE MAIN BODY(F) ,AND TIGHTEN THE HEXANGULAR SCREW IN THE SIDE DESIRE HOLE BY ALLEN WRENCH(J) .REPEAT THE SAME OPERATION ON THE ROD (D1)AND (D2).
- 6.REMOVE THE MOUNTING PLATE(A)FROM THE CANOPY(B)BY TURNING COLLAR LOOP(C) IN A COUNTER CLOCKWISE DIRECTION.
- 7.CAREFULLY INSPECT THE PENDANT'S FIXTURE WIRES. THE NEUTRAL FIXTURE WIRE HAS VERY FINE RIDEGS MOLDED INTO ITS PLASTIC COVERING. THE HOT FIXTURE WIRE HAS A SMOOTH COVERING.THE BARE SILVER WIRE IS THE GROUNDED WIRE.
8. ATTACH THE GROUND WIRE FROM THE FIXTURE TO THE GROUND JUNCTION BOX WIRE FROM THE OUTLET (USUALLY GREEN) OR BARE WIRE). FASTEN EACH TOGETHER WITH A PLASTIC WIRE CONNECTOR (H) AND WRAP THE CONNECTION WITH ELECTRICAL TAPE. IF YOUR OUTLET BOX DOES NOT HAVE A GROUND WIRE, INSERT THE GREEN GROUND SCREW INTO THE MOUNTING PLATE (A) FACING DOWN, AND WRAP THE FIXTURE'S BARE GROUND WIRE AROUND THE GROUND SCREW. IT IS IMPERATIVE THAT THE OUTLET BOX IN YOUR HOME BE PROPERLY GROUNDED.
9. CONNECT THE NEUTRAL FIXTURE WIRE TO THE NEUTRAL JUNCTION BOX WIRE (USUALLY WHITE). FASTEN EACH TOGETHER WITH A WIRE CONNECTOR (H) AND WRAP THE .CONNECTION WITH ELECTRICAL TAPE. BE SURE NO STRANDS ARE EXPOSED.
- 10.CONNECT THE HOT FIXTURE WIRE TO THE HOT JUNCTION BOX WIRE (USUALLY BLACK). FASTEN EACH TOGETHER WITH A PLASTIC WIRE CONNECTOR (H) AND WRAP THE CONNECTION WITH ELECTRICAL TAPE. BE SURE NO WIRE STRANDS ARE EXPOSED. DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
11. GENTLY TRUCK THE WIRE CONNECTIONS NEATLY INTO THE CEILING JUNCTION BOX.
- 12.ATTACH THE MOUNTING PLATE (A) WITH NIPPLE TO THE CEILING OUTLET BOX USING THE ENCLOSED MOUNTING SCREWS (I) AND TIGHTEN SCREWS WITH A SCREWDRIVER.
13. PUSH COLLAR LOOP IN CANOPY (B) AND THREAD ONTO NIPPLE IN MOUNTING PLATE (A) BY TURNING IN A CLOCKWISE
- 14.SCREW ROD (D1) TO CANOPY (C), USING HEXANGULAR SCREW AND ALLEN WRENCH(I)
BE SURE ALL THE HEXANGULAR SCREWS WERE TIGHT ENOUGH.
15. INSERT EIGHT TYPE B 40W BULB (NOT INCLUDED) INTO THE SOCKETS. DO NOT EXCEED SPECIFIED WATTAGE.

CARE & MAINTENANCE

FOR CUSTOMER SERVICE QUESTION CALL 1.888.488.8866 **DISCLAIMERS**

ARTERIOS HOME:972.488.9800

WE RECOMMEND THE INSTALLATION OF THIS ELECTRICAL LIGHT FIXTURE TO BE DONE BY A LICENSED ELECTRICIAN.

ARTERIOS CONTRACT:972.488.9800 EXT.321

ARTERIOS

ASSEMBLY INSTRUCTIONS

ITEM NUMBER#89029|Waldorf Large Chandelier

ITEM DESCRIPTION

MATERIAL TYPE: STEEL.GLASS FINISH :ANTIQUE BRASS.CLEAR TOP COAT/SEALANT:
SOCKET TYPE: E12 BAKELITE SOCKET QTY:8
BULB TYPE: TYPE B BULB WATTAGE: 40W VOLTAGE:110V-120V
ITEM NET WEIGHT:



UL COMPLAINT
INSTALLATION ENVIRONMENT:SUITABLE FOR DAMP LOCATIONS

NOTE:

- *YOUR PRODUCT(S) MAY BE PACKED IN MORE THAN ONE CARTON
- *THIS ITEM MAY REQUIRE PERIODIC TIGHTENING

METAL "ARROW" AND RIDGE GLASS ASSEMBLY INSTRUCTIONS:

PLS take the metal "arrows"and ridge glass from the package,and assemble as bellow steps:

(1 means layer 1 threading pitches on the sphere box, 2 means layer 2, 3 means layer 3

L means longer metal arrow , M means medium arrow , S means short arrow, G means ridge glass

* means socket ,already assembled).

1: L G S L G S

2: * L M * L M * L M * L M

3: L G S L G S L G S L G S L G S



4: L M S L M S L M S L M S L M S L M S

5: L G S L G S L G S L G S L G S

6: * L M * L M * L M * L M

7: L G S L G S

8: L



CARE & MAINTENANCE

FOR CUSTOMER SERVICE QUESTION CALL 1.888.488.8866 **DISCLAIMERS**

ARTERIOS HOME:972.488.9800

WE RECOMMEND THE INSTALLATION OF THIS ELECTRICAL LIGHT FIXTURE TO BE DONE BY A LICENSED ELECTRICIAN.

ARTERIOS CONTRACT:972.488.9800 EXT.321

ARTERIOS