

ASSEMBLY INSTRUCTIONS

ITEM# 89066 | Slump Smoke Glass Chandelier

ITEM DESCRIPTION

MATERIAL TYPE: METAL + GLASS FINISH: TEXTURE ANTIQUE BRASS + AB + SLUMP SMOKE GLASS TOP COAT/SEALANT
SOCKET TYPE: E12 CERAMIC SOCKET QTY: 8PCS
BULB TYPE: TYPE B BULB WATTAGE: 60W or CFL 12W or LED 10W VOLTAGE: 110V-120V
ITEM NET WEIGHT:
UL COMPLIANT
INSTALLATION ENVIRONMENT: SUITABLE FOR DAMP LOCATIONS

NOTE:


*YOUR PRODUCT(S) MAY BE PACKED IN MORE THAN ONE CARTON
*THIS ITEM MAY REQUIRE PERIODIC TIGHTENING
*MIN 90°C SUPPLY CONDUCTORS



PARTS

| | | |
|----------|----------------|--------|
| A | MOUNTING PLATE | 1 PC |
| B | CANOPY | 1 PC |
| C | COLLAR LOOP | 1 PC |
| D1.D2.D3 | RODS | 3 PCS |
| E | HEX SCREWS | 6 PCS |
| F | GLASS PANEL | 36 PCS |
| G | LAMP BODY | 1 PC |
| H | SOCKET | 8 PCS |
| I | THUMB-SCREW A | 72PCS |
| L | THUMB-SCREW B | 72PCS |

PRODUCT ASSEMBLY



INCLUDED ASSEMBLY HARDWARE

J mounting screws



K Plastic wire connectors



TOOLS NEEDED (INCLUDED)



ASSEMBLY INSTRUCTIONS

1. REMOVE ALL PACKING CONTENTS AND PARTS FROM THE CARTON(S) CAREFULLY.
2. PLEASE BE SURE YOU HAVE ALL PARTS INDICATED BEFORE YOU BEGIN ASSEMBLY.
3. SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER.
4. SCREW THE ROD(D3) TO LAMP BODY(G) TILL TIGHT, REPEAT THE SAME OPERATION ON THE ROD(D1) AND ROD(D2). WHEN YOU CONNECT THE RODS, LOOSEN THE SMALL HEX SCREWS(E) IN THE SIDE HOLE FIRST THEN TIGHTEN WITH ALLEN WRENCH(U) AFTER ALL RODS ARE CONNECTED. **BE SURE ALL THE HEXANGULAR SCREWS ARE TIGHT ENOUGH.**
5. REMOVE THE MOUNTING PLATE(A) FROM THE CANOPY(B) BY TURNING COLLAR LOOP(C) IN A COUNTER CLOCKWISE DIRECTION.
6. PULL THE ELECTRICAL CORD OF "J BOX" THROUGH THE EXIT HOLE OF THE MOUNTING PLATE.
7. CAREFULLY INSPECT THE FIXTURE WIRES. THE NEUTRAL FIXTURE WIRE HAS VERY FINE RIDGES MOLDED INTO ITS PLASTIC COVERING. THE HOT FIXTURE WIRE HAS A SMOOTH COVERING. THE BARE WIRE IS THE GROUNDED WIRE.
8. ATTACH THE GROUND WIRE FROM THE FIXTURE TO THE GROUND JUNCTION BOX WIRE FROM THE OUTLET (USUALLY GREEN OR BARE WIRE). FASTEN EACH TOGETHER WITH A PLASTIC WIRE CONNECTOR (K) AND WRAP THE CONNECTION WITH ELECTRICAL TAPE. IF YOUR OUTLET BOX DOES NOT HAVE A GROUND WIRE, INSERT THE GREEN GROUND SCREW INTO THE MOUNTING PLATE (A) FACING DOWN, AND WRAP THE FIXTURE'S BARE GROUND WIRE AROUND THE GROUND SCREW. **IT IS IMPERATIVE THAT THE OUTLET BOX IN YOUR HOME BE PROPERLY GROUNDED.**
9. CONNECT THE NEUTRAL FIXTURE WIRE TO THE NEUTRAL JUNCTION BOX WIRE (USUALLY WHITE). FASTEN EACH TOGETHER WITH A WIRE CONNECTOR (K) AND WRAP THE CONNECTION WITH ELECTRICAL TAPE. BE SURE NO STRANDS ARE EXPOSED.
10. CONNECT THE HOT FIXTURE WIRE TO THE HOT JUNCTION BOX WIRE (USUALLY BLACK). FASTEN EACH TOGETHER WITH A PLASTIC WIRE CONNECTOR (K) AND WRAP THE CONNECTION WITH ELECTRICAL TAPE. BE SURE NO WIRE STRANDS ARE EXPOSED. **DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.**
11. GENTLY TUCK THE WIRE CONNECTIONS (K) NEATLY INTO THE JUNCTION BOX.
12. ATTACH THE MOUNTING PLATE (A) WITH NIPPLE TO THE CEILING OUTLET BOX USING THE ENCLOSED MOUNTING SCREWS (J) AND TIGHTEN SCREWS WITH A SCREWDRIVER.
13. PUSH COLLAR LOOP(C) IN CANOPY (B) AND THREAD ONTO THE NIPPLE IN MOUNTING PLATE (A) BY TURNING IN A CLOCKWISE DIRECTION.
14. ATTACHED THE GLASS PANEL (F) ON THE LAMP BODY (G), THEN TIGHTEN AND FIX IT WITH 2 SETS OF THE THUMB-SCREW A (I) AND THUMB-SCREW B (L). REPEAT THE SAME OPERATION ON THE OTHER GLASS PANELS (F).
15. INSERT 8 TYPE B 60W BULBS (OR /CFL 12W OR /LED 10W, NOT INCLUDED) INTO THE SOCKET (H). **DO NOT EXCEED THE SPECIFIED WATTAGE.**
16. RESTORE POWER TO THE JUNCTION BOX AND TEST FIXTURE.

CARE & MAINTENANCE

DUST WITH A DRY CLOTH.

FOR CUSTOMER SERVICE QUESTIONS CALL 1.888.488.8866

ARTERIORES HOME: 972.488.9800

ARTERIORES CONTRACT: 972.488.9800 EXT.321

DISCLAIMERS

WE RECOMMEND THE INSTALLATION OF THIS ELECTRICAL LIGHT FIXTURE TO BE DONE BY A LICENSED ELECTRICIAN.

ARTERIORES