



## 4860N

40<sup>1</sup>/<sub>2</sub>" x 59" x 23"

**Installation:** Drop-in  
cannot be under mounted

### GENERAL SPECIFICATIONS:

**Material** Acrylic

**Plumbed Weight :** 140lbs / 64kg

**Soaker Weight :** 110 lbs / 50kg

**Average Fill:** 45 gal to above jet level

### ELECTRICAL SPECIFICATIONS:

Required Electrical

Service 110 Volt

Air Bath or Whirlpool

1-15 amp GFCI

Whirlpool with Inline Heater

1-20 amp GFCI

Dual Bath

1-20 amp GFCI

Soaker

### PACKAGES AND OPTIONS

Hydrotherapy Package	Package Contents	Part #
<b>Soaker</b>	soaking bath - no jets, textured bottom	4860NS
<b>Whirlpool</b>	8point-massage jets, 1-hp pump, textured bottom	4860NH
<b>Air Bath</b>	26 air jets, air blower, textured bottom	4860NA
<b>Dual Bath</b>	8 point-massage jets, 1-hp pump, 26 air jets, air blower, textured bottom	4860ND

### OPTIONS

Colors Available - White Biscuit

Quick Ship - reduces lead time - call for availability

Inline Heater with Pump - Whirlpool or Dual Bath

Lift & Turn Drain Kit -Chrome,Brushed Nickel, White

### IMPORTANT INFORMATION

- Before ordering or installing, please consider future access to equipment.
- Add bedding compound to fully level and support bottom of tub.
- Tubs equipped with an air bath or a pre-leveled foam base are designed to rest on the floor without bedding compound, provided the floor is level.
- Please measure tub on-site before building tub decking.
- Jet, pump & blower locations are predetermined and cannot be changed.

- Suction and control locations may vary.
- Specifications and configurations are subject to change without notice.
- Measurements are +1/2" and are subject to change without notice.
- Measurements herein supersede all others published prior to publication date shown below.