

the SOPORA SINGLE SWING

Single Swing SOPN00A

Sopora possesses proven performance. These enclosures surpass the competition with their quality and additional features.



SHOWER ENCLOSURES

BECAUSE THE SHOWER IS EVERYTHING

www.BascoShowerDoor.com | 800.45.BASCO

Features

- Sopora framed single swing door
- Pull handle
- Pivot hinge with out-swing only
- Tempered glass available in three options
- Easy out-of-square adjustments
- Reversible for left or right installation
- Magnetic latch holds the door securely in place
- Anodized aluminum hardware prevents rusting or corrosion
- Drip system at the bottom of the door includes a channel which returns water back inside the shower

Glass Options

- Clear (CL)
- Obscure (OB)
- AquaGlideXP Clear (XP)

Finish Options

- Chrome (SV)
- Brushed Nickel (BN)
- Oil Rubbed Bronze (OR)



Model

Model	Unit Width (Opening Size*)	Walk-thru Opening	Unit Height
• SOPN00A2963	27 ¹ / ₄ " - 29"	23 ¹⁵ / ₁₆ "	63 ¹ / ₂ "
• SOPN00A3263	31 ¹ / ₈ " - 32 ⁷ / ₈ "	27 ¹³ / ₁₆ "	63 ¹ / ₂ "
• SOPN00A3463	33 ¹ / ₈ " - 34 ⁷ / ₈ "	29 ¹³ / ₁₆ "	63 ¹ / ₂ "
• SOPN00A2967	27 ³ / ₄ " - 29 ¹ / ₂ "	24 ⁷ / ₁₆ "	67"
• SOPN00A3267	31 ¹ / ₈ " - 32 ⁷ / ₈ "	27 ¹³ / ₁₆ "	67"
• SOPN00A3367	33 ¹ / ₈ " - 34 ⁷ / ₈ "	29 ¹³ / ₁₆ "	67"
• SOPN00A2970	27 ³ / ₄ " - 29 ¹ / ₂ "	24 ⁷ / ₁₆ "	70 ¹ / ₂ "
• SOPN00A3470	32 ³ / ₄ " - 34 ¹ / ₂ "	29 ⁷ / ₁₆ "	70 ¹ / ₂ "
• SOPN00A3670	34 ¹ / ₄ " - 36"	30 ¹⁵ / ₁₆ "	70 ¹ / ₂ "

*measurements after walls are finished.

Installation Notes

Install this product according to the installation guide.

Applicable Codes/Standards

Specified model meets or exceeds the following:

- ASTM C1464-06 and ASTM C1048
- Safety criteria CPSC16 CRF 1201 categories 1 & 2 and ANSI Z97.1
- SGCC Certification required.

