

### Features

- Coppia Euro-style Single Swing
- 8" Euro-style through-the-glass pull handle
- 3/8" (10 mm) thick tempered glass available in Clear
- 1" adjustment range provides increased plumb and level tolerance (1/2" adjustment on hinge side, 1/2" adjustment on handle side)
- Anodized aluminum hardware prevents rusting or corrosion
- Fits openings from 23<sup>9</sup>/<sub>16</sub>" to 35<sup>9</sup>/<sub>16</sub>" in two height options
- Reversible for left or right installation
- Installs on fiberglass
- Out swing only

### Glass Options

- 3/8" Clear (CL)
- AquaGlideXP Clear (XP)

### Frame Options

- Chrome (SV)
- Brushed Nickel (BN)
- Oil Rubbed Bronze (OR)



### Installation Notes

Install this product according to the installation guide.

### Applicable Codes/Standards

Specified model meets or exceeds the following:

- ASTM C1464-06 and ASTM C1048
- Safety criteria CPSC16 CRF 1201 categories 1 & 2 and ANSI Z97.1
- SGCC Certification required.

			Glass Weight [lbs]	
Unit Min [in]	Unit Max [in]	Glass Width [in]	72" Unit Height	76" Unit Height
23 9/16	24 9/16	21	53.5	56.5
24 9/16	25 9/16	22	56.1	59.2
25 9/16	26 9/16	23	58.6	61.9
26 9/16	27 9/16	24	61.2	64.6
27 9/16	28 9/16	25	63.7	67.3
28 9/16	29 9/16	26	66.3	70.0
29 9/16	30 9/16	27	68.8	72.6
30 9/16	31 9/16	28	71.4	75.3
31 9/16	32 9/16	29	73.9	78.0
32 9/16	33 9/16	30	76.5	80.7
33 9/16	34 9/16	31	79.0	83.4
34 9/16	35 9/16	32	81.6	86.1

