

## Features

- Infinity semi-frameless bifold door
- Convenient center pull handle
- 1/4" (6.35 mm) thick tempered glass
- Available in four widths from 29<sup>1</sup>/<sub>16</sub>" to 37"
- Each wall jamb has up to 1" of adjustment
- 67" & 72" heights
- Applicable for installation on acrylic, fiberglass or tile
- Can be installed for left or right entry
- Door folds into the shower - perfect for tight spaces



## 1/4" Glass Options

- Clear (CL)
- AquaGlideXP Clear (XP)

## Finish Options

- Chrome (SV)
- Brushed Nickel (BN)



## Model

Model	Unit Width (Opening Size*)	Unit Height
• INFH11A3167	29 <sup>1</sup> / <sub>16</sub> " - 31"	67"
• INFH11A3172	29 <sup>1</sup> / <sub>16</sub> " - 31"	72"
• INFH11A3367	31 <sup>1</sup> / <sub>16</sub> " - 33"	67"
• INFH11A3372	31 <sup>1</sup> / <sub>16</sub> " - 33"	72"
• INFH11A3567	33 <sup>1</sup> / <sub>16</sub> " - 35"	67"
• INFH11A3572	33 <sup>1</sup> / <sub>16</sub> " - 35"	72"
• INFH11A3767	35 <sup>1</sup> / <sub>16</sub> " - 37"	67"
• INFH11A3772	35 <sup>1</sup> / <sub>16</sub> " - 37"	72"

\*Measurements after walls are finished. The largest and smallest part of your opening must be inside the range; choose a range that encompasses your opening widths including out-of-plumb conditions.

## Installation Notes

Install this product according to the installation guide.

## Applicable Codes/Standards

Specified model meets or exceeds the following:

- ASTM C1464-06 and ASTM C1048
- Safety criteria CPSC16 CRF 1201 categories 1 & 2 and ANSIZ97.1
- SGCC Certification required.

